

# Cable duct - CD-HF 100X80

3240363

<https://www.phoenixcontact.com/pc/products/3240363>



Please be informed that the data shown in this PDF document is generated from our Online Catalog. Please find the complete data in the user documentation. Our General Terms of Use for Downloads are valid.

---



Cable duct for installation and mounting in control cabinets, light gray, halogen-free, comprising upper part and mounting base, width: 100 mm, height: 80 mm, length: 2000 mm

---

## Your advantages

- Predetermined breaking point enables tool-free, burr-free removal of bars
- Thanks to its leverage and special cutting geometry, the PPS CD cable duct cutter enables easy, burr-free cutting with minimum effort
- Easy, burr-free cutting with minimum effort using the CUTFOX-CD cable duct cutter
- The wide, diagonal heads of the cable duct bars make it easy to fit the cover and hold it securely in place
- Installed conductors are securely held in place by means of wire retaining clips that can be snapped onto bars on the side
- Plastic body-bound rivets enable easy fixing of cable ducts using the rivet setting tool

# Cable duct - CD-HF 100X80

3240363

<https://www.phoenixcontact.com/pc/products/3240363>



## Commercial Data

Item number	3240363
Packing unit	6 pc
Minimum order quantity	1 pc
Product Key	BE7441
Catalog Page	Page 579 (C-3-2019)
GTIN	4046356508483
Weight per Piece (including packing)	1,666 g
Weight per Piece (excluding packing)	1,666 g
Customs tariff number	39259020
Country of origin	DE

# Cable duct - CD-HF 100X80

3240363

<https://www.phoenixcontact.com/pc/products/3240363>




## Technical Data

### Connection data

Nominal cross section	5577 mm <sup>2</sup>
-----------------------	----------------------

### Dimensions

Dimensional drawing	
Width	100 mm
Height	80 mm
Length	2000 mm

### Material specifications

Color	light grey RAL 7035
Material	PC/ABS
Flammability rating according to UL 94	V0
Components	halogen-free

### Connector

Material	PC/ABS
Material	PC/ABS

### Cable / line

Ambient conditions	
Halogen-free	yes

### Environmental and real-life conditions

Ambient conditions	
Ambient temperature (operation)	-40 °C ... 90 °C


# Cable duct - CD-HF 100X80

3240363

<https://www.phoenixcontact.com/pc/products/3240363>



## Drawings



Base perforation according to DIN EN 50085

# Cable duct - CD-HF 100X80

3240363

<https://www.phoenixcontact.com/pc/products/3240363>



## Approvals



**CSA**

Approval ID: 248269



**UL Recognized**

Approval ID: FILE E 328576



**VDE Zeichengenehmigung**

Approval ID: 40028972



**EAC**

Approval ID: RU C-DE.PB68.W.00513

# Cable duct - CD-HF 100X80

3240363

<https://www.phoenixcontact.com/pc/products/3240363>



## Classifications

### ECLASS

ECLASS-9.0	27400703
ECLASS-10.0.1	27400703
ECLASS-11.0	27400703

### ETIM

ETIM 8.0	EC000012
----------	----------

### UNSPSC

UNSPSC 21.0	39131700
-------------	----------

# Cable duct - CD-HF 100X80

3240363

<https://www.phoenixcontact.com/pc/products/3240363>



## Environmental Product Compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

# Cable duct - CD-HF 100X80

3240363

<https://www.phoenixcontact.com/pc/products/3240363>



## Accessories

### Cover profile

Cover profile - CD-HF COVER 100 - 3240367

<https://www.phoenixcontact.com/pc/products/3240367>



Cover for cable duct, light gray, halogen-free, width: 100 mm, length: 2000 mm

---

### Fastening clip

Fastening clip - RVT-PA 4 - 3240498

<https://www.phoenixcontact.com/pc/products/3240498>



Plastic body-bound rivet, for hole diameter of 4 mm and a material thickness of 1.5 ... 6 mm



# Cable duct - CD-HF 100X80

3240363

<https://www.phoenixcontact.com/pc/products/3240363>



## Fastening clip

Fastening clip - RVT-PA 6 - 3240499

<https://www.phoenixcontact.com/pc/products/3240499>



Plastic body-bound rivet, for hole diameter of 6 mm and a material thickness of 1.5 ... 6 mm

---

## Universal wire retaining clip

Universal wire retaining clip - CD WR - 3240284

<https://www.phoenixcontact.com/pc/products/3240284>



Universal wire holding bracket, perforated, for wiring channels

# Cable duct - CD-HF 100X80

3240363

<https://www.phoenixcontact.com/pc/products/3240363>



## Tool

Tool - UNIFOX-RVT P 4 - 1212478

<https://www.phoenixcontact.com/pc/products/1212478>



Rivet setting tool, for use with RVT-PA 4 plastic body-bound rivets

---

## Tool

Tool - UNIFOX-RVT P 6 - 1212509

<https://www.phoenixcontact.com/pc/products/1212509>



Rivet setting tool, for use with RVT-PA 6 plastic body-bound rivets

---

Phoenix Contact 2022 © - all rights reserved  
<https://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG  
Flachsmarktstraße 8  
D-32825 Blomberg  
+49 (0) 5235-3 00  
[info@phoenixcontact.com](mailto:info@phoenixcontact.com)