

Cable tie - WT-HF 2,6X200 BK

3240741

<https://www.phoenixcontact.com/pc/products/3240741>



Please be informed that the data shown in this PDF document is generated from our Online Catalog. Please find the complete data in the user documentation. Our General Terms of Use for Downloads are valid.



Cable binders for quick and secure bundling, standard version

Cable tie - WT-HF 2,6X200 BK

3240741

<https://www.phoenixcontact.com/pc/products/3240741>



Commercial Data

| | |
|--------------------------------------|---------------------|
| Item number | 3240741 |
| Packing unit | 100 pc |
| Minimum order quantity | 100 pc |
| Product Key | BE7131 |
| Catalog Page | Page 615 (C-3-2019) |
| GTIN | 4046356704571 |
| Weight per Piece (including packing) | 0.628 g |
| Weight per Piece (excluding packing) | 0.62 g |
| Customs tariff number | 39269097 |
| Country of origin | IT |

Cable tie - WT-HF 2,6X200 BK



3240741

<https://www.phoenixcontact.com/pc/products/3240741>

Technical Data

Product properties

| | |
|----------------------|----------------|
| Product type | Cable tie |
| Type | Internal teeth |
| Tensile strength GRP | 80 N |

Dimensions

| | |
|--------|--------|
| Width | 2.6 mm |
| Length | 200 mm |

Material specifications

| | |
|----------------------------------------|--------------------------------|
| Color | black |
| Material | PA 6.6 |
| Flammability rating according to UL 94 | V2 |
| Components | free from silicone and halogen |

Connector

| | |
|----------|--------|
| Material | PA 6.6 |
| Material | PA 6.6 |

Cable / line

Cable structure

| | |
|-------------------------|----------------|
| External cable diameter | 1 mm ... 52 mm |
|-------------------------|----------------|

Mechanical properties

| | |
|------------------|------|
| Tensile strength | 80 N |
|------------------|------|

Environmental and real-life conditions

Ambient conditions

| | |
|-------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Optimum ambient temperature (storage/transport) | 23 °C 50 % Polyamide 6.6 has pronounced hygroscopic properties. It absorbs or releases water in accordance with the level of humidity within its environment. Its properties are ideal when the percentage of water is 2 - 3%. The packaging, which is tailored specifically to the product concerned, contains the optimum level of moisture. To ensure that the ideal properties are maintained, the following points should be observed during storage: Keep product stored inside sealed original packaging, carry out any product processing soon after breaking open the packaging, avoid direct sunlight, avoid direct heat. |
| Ambient temperature (operation) | -40 °C ... 85 °C |
| Ambient temperature (assembly) | -10 °C ... 60 °C |
| Resistance to UV radiation | no |
| Short-term temperature | 110 °C |

Standards and regulations

Cable tie - WT-HF 2,6X200 BK



3240741

<https://www.phoenixcontact.com/pc/products/3240741>

| | |
|----------------------------|----|
| Resistance to UV radiation | no |
|----------------------------|----|

Mounting

| | |
|---------------|-------------------|
| Mounting type | Cannot be removed |
|---------------|-------------------|


Cable tie - WT-HF 2,6X200 BK





3240741


<https://www.phoenixcontact.com/pc/products/3240741>


Approvals


|  UL Recognized | | | | |
|-------------------------------------------------------------------------------------------------|-----------------------|-----------------------|-------------------|-----------------------------|
| | Nominal Voltage U_N | Nominal Current I_N | Cross Section AWG | Cross Section mm^2 |
| External reference | | | - | - |

|  LR | | | | |
|--------------------------------------------------------------------------------------|-----------------------|-----------------------|-------------------|-----------------------------|
| | Nominal Voltage U_N | Nominal Current I_N | Cross Section AWG | Cross Section mm^2 |
| External reference | | | - | - |

|  BV | | | | |
|--------------------------------------------------------------------------------------|-----------------------|-----------------------|-------------------|-----------------------------|
| | Nominal Voltage U_N | Nominal Current I_N | Cross Section AWG | Cross Section mm^2 |
| External reference | | | - | - |

|  RINA | | | | |
|------------------------------------------------------------------------------------------|-----------------------|-----------------------|-------------------|-----------------------------|
| | Nominal Voltage U_N | Nominal Current I_N | Cross Section AWG | Cross Section mm^2 |
| External reference | | | - | - |

|  GL | | | | |
|----------------------------------------------------------------------------------------|-----------------------|-----------------------|-------------------|-----------------------------|
| | Nominal Voltage U_N | Nominal Current I_N | Cross Section AWG | Cross Section mm^2 |
| External reference | | | - | - |

|  DNV | | | | |
|-----------------------------------------------------------------------------------------|-----------------------|-----------------------|-------------------|-----------------------------|
| | Nominal Voltage U_N | Nominal Current I_N | Cross Section AWG | Cross Section mm^2 |
| External reference | | | - | - |

Cable tie - WT-HF 2,6X200 BK

3240741

<https://www.phoenixcontact.com/pc/products/3240741>



Classifications

ECLASS

| | |
|---------------|----------|
| ECLASS-9.0 | 27140702 |
| ECLASS-10.0.1 | 27140702 |
| ECLASS-11.0 | 27140702 |

ETIM

| | |
|----------|----------|
| ETIM 8.0 | EC000046 |
|----------|----------|

UNSPSC

| | |
|-------------|----------|
| UNSPSC 21.0 | 39121700 |
|-------------|----------|

Cable tie - WT-HF 2,6X200 BK

3240741

<https://www.phoenixcontact.com/pc/products/3240741>



Environmental Product Compliance

| | |
|------------|---------------------------------------------------------|
| China RoHS | Environmentally friendly use period: unlimited = EFUP-e |
| | No hazardous substances above threshold values |

Cable tie - WT-HF 2,6X200 BK

3240741

<https://www.phoenixcontact.com/pc/products/3240741>



Accessories

Cable tie tool

Cable tie tool - UNIFOX-CT 4,8 - 1212475

<https://www.phoenixcontact.com/pc/products/1212475>



Cable binder pliers, for plastic cable binders with a width of 2.2 - 4.8 mm, for a material thickness of up to 1.6 mm

Cable tie tool

Cable tie tool - UNIFOX-CT 4,8P - 1212609

<https://www.phoenixcontact.com/pc/products/1212609>



Cable binder pliers, for plastic cable binders with a width of 2.2 - 4.8 mm, for a material thickness of up to 1.6 mm

Phoenix Contact 2022 © - all rights reserved

<https://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG

Flachsmarktstraße 8

D-32825 Blomberg

+49 (0) 5235-3 00

info@phoenixcontact.com