

# End cover - D-ST 2,5-QUATTRO-MT

3038590

<https://www.phoenixcontact.com/de/produkte/3038590>



Please be informed that the data shown in this PDF document is generated from our Online Catalog. Please find the complete data in the user documentation. Our General Terms of Use for Downloads are valid.

---

End cover, length: 84 mm, width: 2.2 mm, height: 36.5 mm, color: gray



# End cover - D-ST 2,5-QUATTRO-MT



3038590

<https://www.phoenixcontact.com/de/produkte/3038590>

## Commercial Data

Item number	3038590
Packing unit	50 pc
Minimum order quantity	1 pc
Sales Key	A1 - Reihenklennen
Product Key	BE2Z1X
Catalog Page	Page 76 (C-1-2019)
GTIN	4017918890865
Weight per Piece (including packing)	3,186 g
Weight per Piece (excluding packing)	3 g
Customs tariff number	85389099
Country of origin	DE

# End cover - D-ST 2,5-QUATTRO-MT



3038590

<https://www.phoenixcontact.com/de/produkte/3038590>

## Technical Data

### Product properties

Product type	End cover
--------------	-----------

### Ambient conditions

Ambient temperature (operation)	-60 °C ... 105 °C (max. short-term operating temperature RTI Elec.)
Ambient temperature (storage/transport)	-25 °C ... 60 °C (for a short time, not exceeding 24 h, -60 °C to +70 °C)
Ambient temperature (assembly)	-5 °C ... 70 °C
Ambient temperature (actuation)	-5 °C ... 70 °C
Permissible humidity (storage/transport)	30 % ... 70 %

### Material specifications

Color	gray
Material	PA
Flammability rating according to UL 94	V0
Static insulating material application in cold	-60 °C
Temperature index of insulation material (DIN EN 60216-1 (VDE 0304-21))	125 °C
Relative insulation material temperature index (Elec., UL 746 B)	130 °C
Fire protection for rail vehicles (DIN EN 45545-2) R22	HL 1 - HL 3
Fire protection for rail vehicles (DIN EN 45545-2) R23	HL 1 - HL 3
Fire protection for rail vehicles (DIN EN 45545-2) R24	HL 1 - HL 3
Fire protection for rail vehicles (DIN EN 45545-2) R26	HL 1 - HL 3
Calorimetric heat release NFPA 130 (ASTM E 1354)	27,5 MJ/kg
Surface flammability NFPA 130 (ASTM E 162)	passed
Specific optical density of smoke NFPA 130 (ASTM E 662)	passed
Smoke gas toxicity NFPA 130 (SMP 800C)	passed

### Dimensions

Width	2.2 mm
Height	36.5 mm
Length	84 mm

# End cover - D-ST 2,5-QUATTRO-MT



3038590

<https://www.phoenixcontact.com/de/produkte/3038590>

## Classifications

### ECLASS

ECLASS-9.0	27141133
ECLASS-10.0.1	27141133
ECLASS-11.0	27141133

### ETIM

ETIM 8.0	EC000886
----------	----------

### UNSPSC

UNSPSC 21.0	39121400
-------------	----------

# End cover - D-ST 2,5-QUATTRO-MT



3038590

<https://www.phoenixcontact.com/de/produkte/3038590>

## Environmental Product Compliance

China RoHS

Environmentally friendly use period: unlimited = EFUP-e

No hazardous substances above threshold values

Phoenix Contact 2022 © - all rights reserved

<https://www.phoenixcontact.com>

PHOENIX CONTACT Deutschland GmbH

Flachmarktstraße 8

D-32825 Blomberg

+49 52 35/3-1 20 00

[info@phoenixcontact.de](mailto:info@phoenixcontact.de)