

Filler plugs - ME B-17,5 MSTBO RD

2706881

<https://www.phoenixcontact.com/de/produkte/2706881>



Please be informed that the data shown in this PDF document is generated from our Online Catalog. Please find the complete data in the user documentation. Our General Terms of Use for Downloads are valid.



DIN rail housing, Filler plug for unoccupied terminal points (MSTBO), width: 15 mm, height: 19.05 mm, depth: 12.3 mm, color: red (3001)

Your advantages

- Easy, tool-free mounting
- Flammability rating V0 in accordance with UL 94

Filler plugs - ME B-17,5 MSTBO RD



2706881

<https://www.phoenixcontact.com/de/produkte/2706881>

Commercial Data

Item number	2706881
Packing unit	10 pc
Minimum order quantity	10 pc
Note	Made to Order (non-returnable)
Sales Key	F1 - Elektronikgehäuse
Product Key	ACHAAZ
GTIN	4017918847418
Weight per Piece (including packing)	1,14 g
Weight per Piece (excluding packing)	0,85 g
Customs tariff number	39269097
Country of origin	DE

Filler plugs - ME B-17,5 MSTBO RD



2706881

<https://www.phoenixcontact.com/de/produkte/2706881>

Technical Data

Product properties

Product type	Filler plug
Type	Filler plug for unoccupied terminal points (MSTBO)
Housing type	DIN rail housing
Ventilation openings present	no
Housing series	ME

Dimensions

Width	15 mm
Height	19.05 mm
Depth	12.3 mm

Material specifications

Color	red (3001)
Flammability rating according to UL 94	V0
CTI according to IEC 60112	600
Surface characteristics	untreated
Housing material	Polyamide

Environmental and real-life conditions

Vibration test

Specification	IEC 60068-2-6:2007-12
Frequency	10 - 150 - 10 Hz
Sweep speed	1 octave/min
Amplitude	0.15 mm (10 - 58.1 Hz)
Acceleration	2g (58.1 - 150 Hz)
Test duration per axis	2.5 h
Test directions	X-, Y- and Z-axis

Glow-wire test

Specification	DIN EN 60695-2-11 (VDE 0471-2-11):2014-11
Temperature	850 °C
Time of exposure	30 s

Thermal stability / ball thrust test

Specification	IEC 60695-10-2:2014-02
Temperature	125 °C
Test duration	1 h
Force	20 N

Mechanical strength / tumbling barrel

Specification	IEC 60998-1:2002-12
---------------	---------------------

Filler plugs - ME B-17,5 MSTBO RD



2706881

<https://www.phoenixcontact.com/de/produkte/2706881>

Height of fall	50 cm
Frequency	10

Shocks

Specification	IEC 60068-2-27:2008-02
Pulse shape	Half-sine
Acceleration	15g
Shock duration	11 ms
Number of shocks per direction	3
Test directions	X-, Y- and Z-axis (pos. and neg.)

Degree of protection (IP code)

Specification	IEC 60529:1989-11 + AMD 1:1999-11 + AMD 2:2013-08
---------------	---

Ambient conditions

Max. IP code to attain	IP20
Ambient temperature (operation)	-40 °C ... 105 °C (depending on power dissipation)
Ambient temperature (storage/transport)	-40 °C ... 55 °C
Ambient temperature (assembly)	-5 °C ... 100 °C
Relative humidity (storage/transport)	80 %

Mounting

Mounting type	Latching
---------------	----------

Filler plugs - ME B-17,5 MSTBO RD

2706881

<https://www.phoenixcontact.com/de/produkte/2706881>



Approvals



UL Recognized

Approval ID: FILE E 240868

Filler plugs - ME B-17,5 MSTBO RD



2706881

<https://www.phoenixcontact.com/de/produkte/2706881>

Classifications

ECLASS

ECLASS-9.0	27182702
ECLASS-10.0.1	27182702
ECLASS-11.0	27182702

ETIM

ETIM 8.0	EC001031
----------	----------

UNSPSC

UNSPSC 21.0	31261500
-------------	----------

Filler plugs - ME B-17,5 MSTBO RD



2706881

<https://www.phoenixcontact.com/de/produkte/2706881>

Environmental Product Compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

Phoenix Contact 2022 © - all rights reserved
<https://www.phoenixcontact.com>

PHOENIX CONTACT Deutschland GmbH
Flachmarktstraße 8
D-32825 Blomberg
+49 52 35/3-1 20 00
info@phoenixcontact.de