

Feed-through terminal block - STS 6-TWIN

3038150

<https://www.phoenixcontact.com/de/produkte/3038150>

Please be informed that the data shown in this PDF document is generated from our Online Catalog. Please find the complete data in the user documentation. Our General Terms of Use for Downloads are valid.



Feed-through terminal block, nom. voltage: 800 V, nominal current: 41 A, connection method: Spring-cage connection, 1 level, Rated cross section: 6 mm², cross section: 0.2 mm² - 10 mm², mounting type: NS 35/7,5, NS 35/15, color: gray

Your advantages

- Cross connection to adjacent feed-through terminal blocks with the consistent FBS ... plug-in bridge system
- Same shape and pitch as the feed-through terminal blocks

Feed-through terminal block - STS 6-TWIN



3038150

<https://www.phoenixcontact.com/de/produkte/3038150>

Commercial Data

| | |
|--------------------------------------|---------------------|
| Item number | 3038150 |
| Packing unit | 50 pc |
| Minimum order quantity | 1 pc |
| Sales Key | A1 - Reihenklennen |
| Product Key | BE2112 |
| Catalog Page | Page 239 (C-1-2019) |
| GTIN | 4017918928971 |
| Weight per Piece (including packing) | 20,318 g |
| Weight per Piece (excluding packing) | 20,318 g |
| Customs tariff number | 85369010 |
| Country of origin | PL |

Feed-through terminal block - STS 6-TWIN



3038150

<https://www.phoenixcontact.com/de/produkte/3038150>

Technical Data

Product properties

| | |
|-----------------------|--------------------------------|
| Product type | Multi-conductor terminal block |
| Number of connections | 3 |
| Number of rows | 1 |
| Potentials | 1 |

Insulation characteristics

| | |
|----------------------|-----|
| Overvoltage category | III |
| Degree of pollution | 3 |

Electrical properties

| | |
|---|--------|
| Rated surge voltage | 8 kV |
| Maximum power dissipation for nominal condition | 1.31 W |

Connection data

| | |
|---------------------------------|-------------------|
| Number of connections per level | 3 |
| Nominal cross section | 6 mm ² |

1 level

| | |
|---|--|
| Stripping length | 12 mm |
| Internal cylindrical gage | A5 |
| Conductor cross section solid | 0.2 mm ² ... 10 mm ² |
| Cross section AWG | 24 ... 8 |
| Conductor cross section flexible | 0.2 mm ² ... 6 mm ² |
| Conductor cross section, flexible [AWG] | 24 ... 10 |
| Flexible conductor cross section flexible (ferrule, w/o plastic sleeve) | 0.25 mm ² ... 6 mm ² |
| Flexible conductor cross section (ferrule with plastic sleeve) | 0.25 mm ² ... 6 mm ² |
| 2 conductors with the same cross section, flexible, with TWIN ferrule with plastic sleeve | 0.5 mm ² ... 1.5 mm ² |
| Nominal current | 41 A |
| Maximum load current | 57 A (with 10 mm ² conductor cross section) |
| Nominal voltage | 800 V |
| Nominal cross section | 6 mm ² |

Dimensions

| | |
|------------------|---------|
| Width | 8.2 mm |
| End cover width | 2.2 mm |
| Height NS 35/15 | 57.5 mm |
| Height NS 35/7,5 | 50 mm |
| Length | 70 mm |

Material specifications

Feed-through terminal block - STS 6-TWIN



3038150

<https://www.phoenixcontact.com/de/produkte/3038150>

| | |
|---|-------------|
| Color | gray |
| Flammability rating according to UL 94 | V0 |
| Insulating material group | I |
| Insulating material | PA |
| Static insulating material application in cold | -60 °C |
| Temperature index of insulation material (DIN EN 60216-1 (VDE 0304-21)) | 125 °C |
| Relative insulation material temperature index (Elec., UL 746 B) | 130 °C |
| Fire protection for rail vehicles (DIN EN 45545-2) R22 | HL 1 - HL 3 |
| Fire protection for rail vehicles (DIN EN 45545-2) R23 | HL 1 - HL 3 |
| Fire protection for rail vehicles (DIN EN 45545-2) R24 | HL 1 - HL 3 |
| Fire protection for rail vehicles (DIN EN 45545-2) R26 | HL 1 - HL 3 |
| Calorimetric heat release NFPA 130 (ASTM E 1354) | 27,5 MJ/kg |
| Surface flammability NFPA 130 (ASTM E 162) | passed |
| Specific optical density of smoke NFPA 130 (ASTM E 662) | passed |
| Smoke gas toxicity NFPA 130 (SMP 800C) | passed |

Electrical tests

Surge voltage test

| | |
|-----------------------|-------------|
| Test voltage setpoint | 9.8 kV |
| Result | Test passed |

Temperature-rise test

| | |
|---|-------------------------------------|
| Requirement temperature-rise test | Increase in temperature \leq 45 K |
| Result | Test passed |
| Short-time withstand current 6 mm ² | 0.72 kA |
| Short-time withstand current 10 mm ² | 1.2 kA |
| Result | Test passed |

Power-frequency withstand voltage

| | |
|-----------------------|-------------|
| Test voltage setpoint | 2.2 kV |
| Result | Test passed |

Mechanical properties

Mechanical data

| | |
|-----------------|-----|
| Open side panel | Yes |
|-----------------|-----|

Mechanical tests

Mechanical strength

| | |
|--------|-------------|
| Result | Test passed |
|--------|-------------|

Attachment on the carrier

| | |
|-------------------------|-------|
| DIN rail/fixing support | NS 35 |
| Test force setpoint | 5 N |

Feed-through terminal block - STS 6-TWIN



3038150

<https://www.phoenixcontact.com/de/produkte/3038150>

| | |
|--------|-------------|
| Result | Test passed |
|--------|-------------|

Test for conductor damage and slackening

| | |
|--------------------------------|------------------------------|
| Rotation speed | 10 rpm |
| Revolutions | 135 |
| Conductor cross section/weight | 0.2 mm ² / 0.3 kg |
| | 6 mm ² / 1.4 kg |
| | 10 mm ² / 2 kg |
| Result | Test passed |

Environmental and real-life conditions

Aging

| | |
|--------------------|-------------|
| Temperature cycles | 192 |
| Result | Test passed |

Needle-flame test

| | |
|------------------|-------------|
| Time of exposure | 30 s |
| Result | Test passed |

Oscillation/broadband noise

| | |
|------------------------|--|
| Specification | DIN EN 50155 (VDE 0115-200):2008-03 |
| Spectrum | Service life test category 2, bogie-mounted |
| Frequency | $f_1 = 5 \text{ Hz}$ to $f_2 = 250 \text{ Hz}$ |
| ASD level | 6.12 (m/s ²) ² /Hz |
| Acceleration | 3.12g |
| Test duration per axis | 5 h |
| Test directions | X-, Y- and Z-axis |
| Result | Test passed |

Shocks

| | |
|--------------------------------|-------------------------------------|
| Specification | DIN EN 50155 (VDE 0115-200):2008-03 |
| Pulse shape | Half-sine |
| Acceleration | 30g |
| Shock duration | 18 ms |
| Number of shocks per direction | 3 |
| Test directions | X-, Y- and Z-axis (pos. and neg.) |
| Result | Test passed |

Ambient conditions

| | |
|--|---|
| Ambient temperature (operation) | -60 °C ... 105 °C (max. short-term operating temperature RTI Elec.) |
| Ambient temperature (storage/transport) | -25 °C ... 60 °C (for a short time, not exceeding 24 h, -60 °C to +70 °C) |
| Ambient temperature (assembly) | -5 °C ... 70 °C |
| Ambient temperature (actuation) | -5 °C ... 70 °C |
| Permissible humidity (storage/transport) | 30 % ... 70 % |

Feed-through terminal block - STS 6-TWIN



3038150

<https://www.phoenixcontact.com/de/produkte/3038150>

Standards and regulations

| | |
|----------------------------------|---------------|
| Connection in acc. with standard | IEC 60947-7-1 |
|----------------------------------|---------------|

Mounting

| | |
|---------------|-----------|
| Mounting type | NS 35/7,5 |
| | NS 35/15 |

Feed-through terminal block - STS 6-TWIN

3038150

<https://www.phoenixcontact.com/de/produkte/3038150>

Drawings

Circuit diagram




Feed-through terminal block - STS 6-TWIN





3038150

<https://www.phoenixcontact.com/de/produkte/3038150>

Approvals

|  CSA Approval ID: 13631 | | | | |
|--|-----------------------|-----------------------|-------------------|-----------------------------|
| | Nominal Voltage U_N | Nominal Current I_N | Cross Section AWG | Cross Section mm^2 |
| Use group B | 600 V | 50 A | 24 - 8 | - |
| Use group C | 600 V | 50 A | 24 - 8 | - |

|  IECEE CB Scheme Approval ID: DE1-62704 | | | | |
|--|--|--|--|--|
|--|--|--|--|--|

|  EAC Approval ID: RU C-DE.BL08.B.00644 | | | | |
|---|--|--|--|--|
|---|--|--|--|--|

|  LR Approval ID: 06/20022 | | | | |
|--|--|--|--|--|
|--|--|--|--|--|

|  NK Approval ID: 06ME279 | | | | |
|---|-----------------------|-----------------------|-------------------|-----------------------------|
| | Nominal Voltage U_N | Nominal Current I_N | Cross Section AWG | Cross Section mm^2 |
| | | | - | - |

|  RS Approval ID: 17.00013.272 | | | | |
|--|--|--|--|--|
|--|--|--|--|--|

|  BV Approval ID: 27725/A0 BV | | | | |
|---|-----------------------|-----------------------|-------------------|-----------------------------|
| | Nominal Voltage U_N | Nominal Current I_N | Cross Section AWG | Cross Section mm^2 |
| | | | - | - |

|  VDE Zeichengenehmigung Approval ID: 40038073 | | | | |
|--|-----------------------|-----------------------|-------------------|-----------------------------|
| | Nominal Voltage U_N | Nominal Current I_N | Cross Section AWG | Cross Section mm^2 |
| | 800 V | 41 A | - | 0.2 - 6 |


| ABS Approval ID: 21-2158220-PDA | | | | |
|---|--|--|--|--|
|---|--|--|--|--|

Feed-through terminal block - STS 6-TWIN



3038150

<https://www.phoenixcontact.com/de/produkte/3038150>

|  cULus Recognized Approval ID: E60425 | | | | |
|--|-----------------------|-----------------------|-------------------|-----------------------------|
| | Nominal Voltage U_N | Nominal Current I_N | Cross Section AWG | Cross Section mm^2 |
| Use group B | | | | |
| | 600 V | 50 A | 24 - 8 | - |
| Use group C | | | | |
| | 600 V | 50 A | 24 - 8 | - |

| DNV Approval ID: TAE00001CS | | | | |
|---------------------------------------|-----------------------|-----------------------|-------------------|-----------------------------|
| | Nominal Voltage U_N | Nominal Current I_N | Cross Section AWG | Cross Section mm^2 |
| | | | - | - |

Feed-through terminal block - STS 6-TWIN



3038150

<https://www.phoenixcontact.com/de/produkte/3038150>

Classifications

ECLASS

| | |
|---------------|----------|
| ECLASS-9.0 | 27141120 |
| ECLASS-10.0.1 | 27141120 |
| ECLASS-11.0 | 27141120 |

ETIM

| | |
|----------|----------|
| ETIM 8.0 | EC000897 |
|----------|----------|

UNSPSC

| | |
|-------------|----------|
| UNSPSC 21.0 | 39121400 |
|-------------|----------|

Feed-through terminal block - STS 6-TWIN



3038150

<https://www.phoenixcontact.com/de/produkte/3038150>

Environmental Product Compliance

| | |
|------------|---|
| China RoHS | Environmentally friendly use period: unlimited = EFUP-e |
| | No hazardous substances above threshold values |

Feed-through terminal block - STS 6-TWIN

3038150

<https://www.phoenixcontact.com/de/produkte/3038150>

Accessories

i Note: Applying some accessories below might limit this product.

Plug-in bridge

Plug-in bridge - FBS 2-8 - 3030284

<https://www.phoenixcontact.com/de/produkte/3030284>



Plug-in bridge, pitch: 8.2 mm, color: red

i Max. current carrying capacity: 41 A

Plug-in bridge

Plug-in bridge - FBS 3-8 - 3030297

<https://www.phoenixcontact.com/de/produkte/3030297>



Plug-in bridge, pitch: 8.2 mm, color: red

i Max. current carrying capacity: 41 A

Feed-through terminal block - STS 6-TWIN

3038150

<https://www.phoenixcontact.com/de/produkte/3038150>


Plug-in bridge

Plug-in bridge - FBS 4-8 - 3030307

<https://www.phoenixcontact.com/de/produkte/3030307>



Plug-in bridge, pitch: 8.2 mm, color: red

 Max. current carrying capacity: 41 A


Plug-in bridge

Plug-in bridge - FBS 5-8 - 3030310

<https://www.phoenixcontact.com/de/produkte/3030310>



Plug-in bridge, pitch: 8.2 mm, color: red

 Max. current carrying capacity: 41 A

Feed-through terminal block - STS 6-TWIN

3038150

<https://www.phoenixcontact.com/de/produkte/3038150>


Plug-in bridge

Plug-in bridge - FBS 10-8 - 3030323

<https://www.phoenixcontact.com/de/produkte/3030323>



Plug-in bridge, pitch: 8.2 mm, color: red

 Max. current carrying capacity: 41 A


Plug-in bridge

Plug-in bridge - FBS 6-8 - 3032470

<https://www.phoenixcontact.com/de/produkte/3032470>



Plug-in bridge, pitch: 8.2 mm, color: red

 Max. current carrying capacity: 41 A

Feed-through terminal block - STS 6-TWIN

3038150

<https://www.phoenixcontact.com/de/produkte/3038150>


Plug-in bridge

Plug-in bridge - FBS 2-8 CT - 3033830

<https://www.phoenixcontact.com/de/produkte/3033830>



Plug-in bridge, pitch: 8.2 mm, color: orange

 Max. current carrying capacity: 41 A


Plug-in bridge

Plug-in bridge - FBS 3-8 CT - 3033831

<https://www.phoenixcontact.com/de/produkte/3033831>



Plug-in bridge, pitch: 8.2 mm, color: orange

 Max. current carrying capacity: 41 A

Feed-through terminal block - STS 6-TWIN

3038150

<https://www.phoenixcontact.com/de/produkte/3038150>


Plug-in bridge

Plug-in bridge - FBS 4-8 CT - 3033832

<https://www.phoenixcontact.com/de/produkte/3033832>



Plug-in bridge, pitch: 8.2 mm, color: orange

 Max. current carrying capacity: 41 A


Plug-in bridge

Plug-in bridge - FBS 10-8 CT - 3033833

<https://www.phoenixcontact.com/de/produkte/3033833>



Plug-in bridge, pitch: 8.2 mm, color: orange

 Max. current carrying capacity: 41 A

Feed-through terminal block - STS 6-TWIN

3038150

<https://www.phoenixcontact.com/de/produkte/3038150>




Plug-in bridge

Plug-in bridge - FBS 2-8 BU - 3032567

<https://www.phoenixcontact.com/de/produkte/3032567>



Plug-in bridge, pitch: 8.2 mm, color: blue

 Max. current carrying capacity: 41 A

Plug-in bridge

Plug-in bridge - FBS 3-8 BU - 3032570

<https://www.phoenixcontact.com/de/produkte/3032570>



Plug-in bridge, pitch: 8.2 mm, color: blue

 Max. current carrying capacity: 41 A

Feed-through terminal block - STS 6-TWIN

3038150

<https://www.phoenixcontact.com/de/produkte/3038150>




Plug-in bridge

Plug-in bridge - FBS 4-8 BU - 3032583

<https://www.phoenixcontact.com/de/produkte/3032583>



Plug-in bridge, pitch: 8.2 mm, color: blue

 Max. current carrying capacity: 41 A


Plug-in bridge

Plug-in bridge - FBS 5-8 BU - 3032596

<https://www.phoenixcontact.com/de/produkte/3032596>



Plug-in bridge, pitch: 8.2 mm, color: blue

 Max. current carrying capacity: 41 A

Feed-through terminal block - STS 6-TWIN

3038150

<https://www.phoenixcontact.com/de/produkte/3038150>




Plug-in bridge

Plug-in bridge - FBS 6-8 BU - 3032677

<https://www.phoenixcontact.com/de/produkte/3032677>



Plug-in bridge, pitch: 8.2 mm, color: blue

 Max. current carrying capacity: 41 A


Plug-in bridge

Plug-in bridge - FBS 10-8 BU - 3032606

<https://www.phoenixcontact.com/de/produkte/3032606>



Plug-in bridge, pitch: 8.2 mm, color: blue

 Max. current carrying capacity: 41 A

Feed-through terminal block - STS 6-TWIN

3038150

<https://www.phoenixcontact.com/de/produkte/3038150>


Plug-in bridge

Plug-in bridge - FBS 2-8 GY - 3032621

<https://www.phoenixcontact.com/de/produkte/3032621>



Plug-in bridge, pitch: 8.2 mm, color: gray

 Max. current carrying capacity: 41 A


Plug-in bridge

Plug-in bridge - FBS 3-8 GY - 3032622

<https://www.phoenixcontact.com/de/produkte/3032622>



Plug-in bridge, pitch: 8.2 mm, color: gray

 Max. current carrying capacity: 41 A

Feed-through terminal block - STS 6-TWIN

3038150

<https://www.phoenixcontact.com/de/produkte/3038150>


Plug-in bridge

Plug-in bridge - FBS 4-8 GY - 3032635

<https://www.phoenixcontact.com/de/produkte/3032635>

Plug-in bridge, pitch: 8.2 mm, color: gray



 Max. current carrying capacity: 41 A


Plug-in bridge

Plug-in bridge - FBS 5-8 GY - 3032648

<https://www.phoenixcontact.com/de/produkte/3032648>

Plug-in bridge, pitch: 8.2 mm, color: gray



 Max. current carrying capacity: 41 A

Feed-through terminal block - STS 6-TWIN

3038150

<https://www.phoenixcontact.com/de/produkte/3038150>




Plug-in bridge

Plug-in bridge - FBS 6-8 GY - 3032664

<https://www.phoenixcontact.com/de/produkte/3032664>



Plug-in bridge, pitch: 8.2 mm, color: gray

 Max. current carrying capacity: 41 A


Plug-in bridge

Plug-in bridge - FBS 10-8 GY - 3032651

<https://www.phoenixcontact.com/de/produkte/3032651>



Plug-in bridge, pitch: 8.2 mm, color: gray

 Max. current carrying capacity: 41 A

Feed-through terminal block - STS 6-TWIN

3038150

<https://www.phoenixcontact.com/de/produkte/3038150>


Short-circuit connector

Short-circuit connector - FBSRH 2-8 - 3033802

<https://www.phoenixcontact.com/de/produkte/3033802>



Short-circuit connector, pitch: 8.2 mm, color: red

 Max. current carrying capacity: 32 A


Short-circuit connector

Short-circuit connector - FBSRH 3-8 - 3033803

<https://www.phoenixcontact.com/de/produkte/3033803>



Short-circuit connector, pitch: 8.2 mm, color: red

 Max. current carrying capacity: 32 A

Feed-through terminal block - STS 6-TWIN

3038150

<https://www.phoenixcontact.com/de/produkte/3038150>


Short-circuit connector

Short-circuit connector - FBSRH 4-8 - 3033804

<https://www.phoenixcontact.com/de/produkte/3033804>



Short-circuit connector, pitch: 8.2 mm, color: red

 Max. current carrying capacity: 32 A


Plug-in bridge

Plug-in bridge - FBSR 2-8 - 3033808

<https://www.phoenixcontact.com/de/produkte/3033808>



Plug-in bridge, pitch: 8.2 mm, color: red

 Max. current carrying capacity: 32 A

Feed-through terminal block - STS 6-TWIN

3038150

<https://www.phoenixcontact.com/de/produkte/3038150>


Plug-in bridge

Plug-in bridge - FBSR 3-8 - 3001597

<https://www.phoenixcontact.com/de/produkte/3001597>



Plug-in bridge, pitch: 8.2 mm, color: red

 Max. current carrying capacity: 32 A


Plug-in bridge

Plug-in bridge - FBSR 4-8 - 3000585

<https://www.phoenixcontact.com/de/produkte/3000585>



Plug-in bridge, pitch: 8.2 mm, color: red

 Max. current carrying capacity: 32 A

Feed-through terminal block - STS 6-TWIN

3038150

<https://www.phoenixcontact.com/de/produkte/3038150>


Plug-in bridge

Plug-in bridge - FBSR 5-8 - 3033809

<https://www.phoenixcontact.com/de/produkte/3033809>

Plug-in bridge, pitch: 8.2 mm, color: red



 Max. current carrying capacity: 32 A


Plug-in bridge

Plug-in bridge - FBSR 10-8 - 3001599

<https://www.phoenixcontact.com/de/produkte/3001599>

Plug-in bridge, pitch: 8.2 mm, color: red



 Max. current carrying capacity: 32 A

Feed-through terminal block - STS 6-TWIN

3038150

<https://www.phoenixcontact.com/de/produkte/3038150>


Switching jumper

Switching jumper - SB-MER 2-8 - 3000587

<https://www.phoenixcontact.com/de/produkte/3000587>

Switching jumper, pitch: 8.2 mm, color: gray/orange



 Max. current carrying capacity: 25 A


Switching jumper

Switching jumper - SB-MER 3-8 - 3000588

<https://www.phoenixcontact.com/de/produkte/3000588>

Switching jumper, pitch: 8.2 mm, color: gray/orange



 Max. current carrying capacity: 25 A

Feed-through terminal block - STS 6-TWIN

3038150

<https://www.phoenixcontact.com/de/produkte/3038150>




Switching jumper

Switching jumper - SB-MER 4-8 - 3000589

<https://www.phoenixcontact.com/de/produkte/3000589>



Switching jumper, pitch: 8.2 mm, color: gray/orange

 Max. current carrying capacity: 25 A

End cover

End cover - D-ST5 6-TWIN - 3038202

<https://www.phoenixcontact.com/de/produkte/3038202>

End cover, length: 70 mm, width: 2.2 mm, height: 50 mm, color: gray



Feed-through terminal block - STS 6-TWIN

3038150

<https://www.phoenixcontact.com/de/produkte/3038150>

DIN rail perforated

DIN rail perforated - NS 35/ 7,5 PERF 2000MM - 0801733

<https://www.phoenixcontact.com/de/produkte/0801733>



DIN rail perforated, acc. to EN 60715, material: Steel, galvanized, passivated with a thick layer, Standard profile, color: silver, Pack of 25 (50 m)

Partition plate

Partition plate - ATP-ST 6 - 3024481

<https://www.phoenixcontact.com/de/produkte/3024481>



Partition plate, length: 73.5 mm, width: 2 mm, height: 47.2 mm, color: gray

Feed-through terminal block - STS 6-TWIN

3038150

<https://www.phoenixcontact.com/de/produkte/3038150>

DIN rail, unperforated

DIN rail, unperforated - NS 35/ 7,5 UNPERF 2000MM - 0801681

<https://www.phoenixcontact.com/de/produkte/0801681>



DIN rail, unperforated, acc. to EN 60715, material: Steel, galvanized, passivated with a thick layer, Standard profile, color: silver, Pack of 25 (50 m)

Screwdriver

Screwdriver - SZF 2-0,8X4,0 - 1204520

<https://www.phoenixcontact.com/de/produkte/1204520>



Actuation tool, for ST terminal blocks, also suitable for use as a bladed screwdriver, size: 0.8 x 4.0 x 100 mm, 2-component grip, with non-slip grip

Feed-through terminal block - STS 6-TWIN

3038150

<https://www.phoenixcontact.com/de/produkte/3038150>

DIN rail perforated

DIN rail perforated - NS 35/ 7,5 WH PERF 2000MM - 1204119

<https://www.phoenixcontact.com/de/produkte/1204119>



DIN rail perforated, acc. to EN 60715, material: Steel, Galvanized, white passivated, Standard profile, color: silver, Pack of 25 (50 m)

Mounting material

Mounting material - ST-IL - 3039900

<https://www.phoenixcontact.com/de/produkte/3039900>

Operating decal for the ST terminal block



Feed-through terminal block - STS 6-TWIN

3038150

<https://www.phoenixcontact.com/de/produkte/3038150>

DIN rail, unperforated

DIN rail, unperforated - NS 35/ 7,5 WH UNPERF 2000MM-VPE 10 - 1204122

<https://www.phoenixcontact.com/de/produkte/1204122>



DIN rail, unperforated, acc. to EN 60715, material: Steel, Galvanized, white passivated, Standard profile, color: silver, Pack of 10 (20 m)

DIN rail, unperforated

DIN rail, unperforated - NS 35/ 7,5 AL UNPERF 2000MM - 0801704

<https://www.phoenixcontact.com/de/produkte/0801704>



DIN rail, unperforated, acc. to EN 60715, material: Aluminum, uncoated, Standard profile, color: silver, Pack of 25 (50 m)

Feed-through terminal block - STS 6-TWIN

3038150

<https://www.phoenixcontact.com/de/produkte/3038150>

DIN rail perforated

DIN rail perforated - NS 35/ 7,5 ZN PERF 2000MM - 1206421

<https://www.phoenixcontact.com/de/produkte/1206421>



DIN rail perforated, acc. to EN 60715, material: Steel, galvanized, Standard profile, color: silver, Pack of 25 (50 m)

DIN rail, unperforated

DIN rail, unperforated - NS 35/ 7,5 ZN UNPERF 2000MM - 1206434

<https://www.phoenixcontact.com/de/produkte/1206434>



DIN rail, unperforated, acc. to EN 60715, material: Steel, galvanized, Standard profile, color: silver, Pack of 25 (50 m)

Feed-through terminal block - STS 6-TWIN

3038150

<https://www.phoenixcontact.com/de/produkte/3038150>

DIN rail, unperforated

DIN rail, unperforated - NS 35/ 7,5 CU UNPERF 2000MM-VPE 10 - 0801762

<https://www.phoenixcontact.com/de/produkte/0801762>



DIN rail, unperforated, acc. to EN 60715, material: Copper, uncoated, Standard profile, color: copper-colored, Pack of 10 (20 m)

End cap

End cap - NS 35/ 7,5 CAP - 1206560

<https://www.phoenixcontact.com/de/produkte/1206560>

DIN rail end piece, for DIN rail NS 35/7.5



Feed-through terminal block - STS 6-TWIN

3038150

<https://www.phoenixcontact.com/de/produkte/3038150>

Test adapter

Test adapter - PAI-4-FIX BU - 3032729

<https://www.phoenixcontact.com/de/produkte/3032729>



Test adapter, Touch proof against unintentional direct contact according to DIN EN 50274 when plugged in, for 4 mm test plug and terminal blocks with 8.2 mm pitch, color: blue

Test adapter

Test adapter - PAI-4-FIX OG - 3034455

<https://www.phoenixcontact.com/de/produkte/3034455>



4 mm test adapter, for terminal blocks with 8.2 mm pitch

Feed-through terminal block - STS 6-TWIN

3038150

<https://www.phoenixcontact.com/de/produkte/3038150>

Test adapter

Test adapter - PAI-4-FIX YE - 3032745

<https://www.phoenixcontact.com/de/produkte/3032745>



Test adapter, Touch proof against unintentional direct contact according to DIN EN 50274 when plugged in, for 4 mm test plug and terminal blocks with 8.2 mm pitch, color: yellow

Test adapter

Test adapter - PAI-4-FIX RD - 3032732

<https://www.phoenixcontact.com/de/produkte/3032732>



Test adapter, Touch proof against unintentional direct contact according to DIN EN 50274 when plugged in, for 4 mm test plug and terminal blocks with 8.2 mm pitch, color: red

Feed-through terminal block - STS 6-TWIN

3038150

<https://www.phoenixcontact.com/de/produkte/3038150>

Test adapter

Test adapter - PAI-4-FIX GN - 3032758

<https://www.phoenixcontact.com/de/produkte/3032758>



Test adapter, Touch proof against unintentional direct contact according to DIN EN 50274 when plugged in, for 4 mm test plug and terminal blocks with 8.2 mm pitch, color: green

Test adapter

Test adapter - PAI-4-FIX BK - 3032774

<https://www.phoenixcontact.com/de/produkte/3032774>



Test adapter, Touch proof against unintentional direct contact according to DIN EN 50274 when plugged in, for 4 mm test plug and terminal blocks with 8.2 mm pitch, color: black

Feed-through terminal block - STS 6-TWIN

3038150

<https://www.phoenixcontact.com/de/produkte/3038150>

Test adapter

Test adapter - PAI-4-FIX GY - 3032790

<https://www.phoenixcontact.com/de/produkte/3032790>



Test adapter, Touch proof against unintentional direct contact according to DIN EN 50274 when plugged in, for 4 mm test plug and terminal blocks with 8.2 mm pitch, color: gray

Test adapter

Test adapter - PAI-4-FIX VT - 3032761

<https://www.phoenixcontact.com/de/produkte/3032761>



Test adapter, Touch proof against unintentional direct contact according to DIN EN 50274 when plugged in, for 4 mm test plug and terminal blocks with 4.2 mm .. 8.2 mm pitch, color: violet

Feed-through terminal block - STS 6-TWIN

3038150

<https://www.phoenixcontact.com/de/produkte/3038150>

Test adapter

Test adapter - PAI-4-FIX BN - 3032787

<https://www.phoenixcontact.com/de/produkte/3032787>



Test adapter, Touch proof against unintentional direct contact according to DIN EN 50274 when plugged in, for 4 mm test plug and terminal blocks with 8.2 mm pitch, color: brown

Test adapter

Test adapter - PAI-4-FIX WH - 3032797

<https://www.phoenixcontact.com/de/produkte/3032797>



4 mm test adapter, for terminal blocks with 8.2 mm pitch

Feed-through terminal block - STS 6-TWIN

3038150

<https://www.phoenixcontact.com/de/produkte/3038150>

Test adapter

Test adapter - PAIS-4-FIX GY - 3032791

<https://www.phoenixcontact.com/de/produkte/3032791>



Test adapter, Touch proof against unintentional direct contact according to DIN EN 50274 when plugged in, for 4 mm test plug and terminal blocks with 5.2 mm, 6.2 mm, and 8.2 mm pitch, color: gray

Test adapter

Test adapter - PAIS-4-FIX BK - 3032792

<https://www.phoenixcontact.com/de/produkte/3032792>



Test adapter, Touch proof against unintentional direct contact according to DIN EN 50274 when plugged in, for 4 mm test plug and terminal blocks with 5.2 mm, 6.2 mm, and 8.2 mm pitch, color: black

Feed-through terminal block - STS 6-TWIN

3038150

<https://www.phoenixcontact.com/de/produkte/3038150>

Test adapter

Test adapter - PAIS-4-FIX RD - 3032793

<https://www.phoenixcontact.com/de/produkte/3032793>



Test adapter, Do not plug in while the power is connected, for 4 mm test plug and terminal blocks with 5.2 mm, 6.2 mm, and 8.2 mm pitch, color: red

Test adapter

Test adapter - PAIS-4-FIX BU - 3032798

<https://www.phoenixcontact.com/de/produkte/3032798>



Test adapter, Touch proof against unintentional direct contact according to DIN EN 50274 when plugged in, for 4 mm test plug and terminal blocks with 5.2 mm, 6.2 mm, and 8.2 mm pitch, color: blue

Feed-through terminal block - STS 6-TWIN

3038150

<https://www.phoenixcontact.com/de/produkte/3038150>

Test adapter

Test adapter - PAIS-4-FIX YE - 3032799

<https://www.phoenixcontact.com/de/produkte/3032799>



Test adapter, Touch proof against unintentional direct contact according to DIN EN 50274 when plugged in, for 4 mm test plug and terminal blocks with 5.2 mm, 6.2 mm, and 8.2 mm pitch, color: yellow

Test adapter

Test adapter - PAIS-4-FIX GN - 3032801

<https://www.phoenixcontact.com/de/produkte/3032801>



Test adapter, Touch proof against unintentional direct contact according to DIN EN 50274 when plugged in, for 4 mm test plug and terminal blocks with 5.2 mm, 6.2 mm, and 8.2 mm pitch, color: green

Feed-through terminal block - STS 6-TWIN



3038150

<https://www.phoenixcontact.com/de/produkte/3038150>

Test adapter

Test adapter - PAIS-4-FIX VT - 3032802

<https://www.phoenixcontact.com/de/produkte/3032802>



Test adapter, Touch proof against unintentional direct contact according to DIN EN 50274 when plugged in, for 4 mm test plug and terminal blocks with 5.2 mm, 6.2 mm, and 8.2 mm pitch, color: violet

End clamp

End clamp - E/AL-NS 35 - 1201662

<https://www.phoenixcontact.com/de/produkte/1201662>



End clamp, for end support of UKH 50 to UKH 240, is pushed onto DIN rail NS 35 and fixed with 2 screws, width: 10 mm, color: aluminum

Phoenix Contact 2022 © - all rights reserved
<https://www.phoenixcontact.com>

PHOENIX CONTACT Deutschland GmbH
Flachsmarktstraße 8
D-32825 Blomberg
+49 52 35/3-1 20 00
info@phoenixcontact.de