

# Cable reel - SAC-4P-100,0-PUR/0,34

1501663

<https://www.phoenixcontact.com/pc/products/1501663>



Please be informed that the data shown in this PDF document is generated from our Online Catalog. Please find the complete data in the user documentation. Our General Terms of Use for Downloads are valid.

---



By the meter, Cable reel, PUR halogen-free, black-gray RAL 7021, 4-wire, color single wire: brown, white, blue, black, cable length: 100 m

# Cable reel - SAC-4P-100,0-PUR/0,34



1501663

<https://www.phoenixcontact.com/pc/products/1501663>

## Commercial Data

Item number	1501663
Packing unit	1 pc
Minimum order quantity	1 pc
Product Key	BF1LBA
Catalog Page	Page 302 (C-2-2019)
GTIN	4017918813352
Weight per Piece (including packing)	2,730.7 g
Weight per Piece (excluding packing)	2,730.7 g
Customs tariff number	85444995
Country of origin	DE

# Cable reel - SAC-4P-100,0-PUR/0,34



1501663

<https://www.phoenixcontact.com/pc/products/1501663>

## Technical Data

### Product properties

Product type	Cable by the meter
Number of positions	4
Application	Connector
Shielded	no

### Cable / line

Cable length	100 m
Cable weight	30 kg/km
UL AWM Style	20549 / 10493 (80°C/300 V)
Number of positions	4
Shielded	no
Cable type	PUR halogen-free black [PUR]
Conductor structure signal line	42x 0.10 mm
AWG signal line	22
Conductor cross section	4x 0.34 mm <sup>2</sup>
Wire diameter incl. insulation	1.27 mm ±0.02 mm
External cable diameter	4.2 mm ±0.15 mm
Outer sheath, material	PUR
External sheath, color	black-gray RAL 7021
Conductor material	Bare Cu litz wires
Material wire insulation	PP
Single wire, color	brown, white, blue, black
Thickness, insulation	≥ 0.21 mm
Thickness, outer sheath	approx. 0.5 mm
Overall twist	4 wires, twisted
Max. conductor resistance	≤ 58 Ω/km
Insulation resistance	≥ 1 GΩ*km
Nominal voltage, cable	≤ 300 V
Test voltage	≥ 3000 V
Minimum bending radius, fixed installation	5 x D
Minimum bending radius, flexible installation	10 x D
Max. bending cycles	10000000
Halogen-free	in accordance with DIN VDE 0472 part 815 in accordance with DIN EN 50267-2-1
Flame resistance	in accordance with UL 758/1581 FT2 DIN EN 60332-2-2 (20 s)
Resistance to oil	in accordance with DIN EN 60811-2-1
Other resistance	Highly resistant to acids, alkaline solutions and solvents hydrolysis and microbe resistant partly UV-resistant in accordance with DIN EN ISO 4892-2-A

# Cable reel - SAC-4P-100,0-PUR/0,34



1501663

<https://www.phoenixcontact.com/pc/products/1501663>

Special properties	Low adhesion
	abrasion-resistant
	Flexible cable conduit capable
	Silicone-free
	Free of substances which would hinder coating with paint or varnish
Ambient temperature (operation)	flexible
	-40 °C ... 80 °C (cable, fixed installation)
	-25 °C ... 80 °C (Cable, flexible installation)

# Cable reel - SAC-4P-100,0-PUR/0,34

1501663

<https://www.phoenixcontact.com/pc/products/1501663>



## Approvals



**EAC**

Approval ID: RU D-DE.HB35.B.00371

# Cable reel - SAC-4P-100,0-PUR/0,34



1501663

<https://www.phoenixcontact.com/pc/products/1501663>

## Classifications

### ECLASS

ECLASS-9.0	27062011
ECLASS-10.0.1	27061801
ECLASS-11.0	27061801

### ETIM

ETIM 8.0	EC003249
----------	----------

### UNSPSC

UNSPSC 21.0	26121600
-------------	----------

# Cable reel - SAC-4P-100,0-PUR/0,34



1501663

<https://www.phoenixcontact.com/pc/products/1501663>

## Environmental Product Compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

# Cable reel - SAC-4P-100,0-PUR/0,34

1501663

<https://www.phoenixcontact.com/pc/products/1501663>



## Accessories

### Stripping tool

Stripping tool - WIREFOX SAC - 1212623

<https://www.phoenixcontact.com/pc/products/1212623>



Stripping pliers, for halogen-free sensor/actuator cables (SAC cables), with PUR and PVC insulation, from Ø of 4.4 to 7 mm, any stripping length

---

Phoenix Contact 2022 © - all rights reserved  
<https://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG  
Flachsmarktstraße 8  
D-32825 Blomberg  
+49 (0) 5235-3 00  
[info@phoenixcontact.com](mailto:info@phoenixcontact.com)