

Cable tie - WT-HF 2,5X98

3240732

<https://www.phoenixcontact.com/pc/products/3240732>



Please be informed that the data shown in this PDF document is generated from our Online Catalog. Please find the complete data in the user documentation. Our General Terms of Use for Downloads are valid.

Cable binders for quick and secure bundling, standard version



Cable tie - WT-HF 2,5X98

3240732

<https://www.phoenixcontact.com/pc/products/3240732>



Commercial Data

Item number	3240732
Packing unit	100 pc
Minimum order quantity	100 pc
Product Key	BE7131
Catalog Page	Page 614 (C-3-2019)
GTIN	4046356704489
Weight per Piece (including packing)	0.319 g
Weight per Piece (excluding packing)	0.28 g
Customs tariff number	39269097
Country of origin	PL

Cable tie - WT-HF 2,5X98



3240732

<https://www.phoenixcontact.com/pc/products/3240732>

Technical Data

Product properties

Product type	Cable tie
Type	Internal teeth
Tensile strength GRP	80 N

Dimensions

Width	2.5 mm
Length	98 mm

Material specifications

Color	transparent
Material	PA 6.6
Flammability rating according to UL 94	V2
Components	free from silicone and halogen

Connector

Material	PA 6.6
Material	PA 6.6

Cable / line

Cable structure

External cable diameter	1 mm ... 21 mm
-------------------------	----------------

Mechanical properties

Tensile strength	80 N
------------------	------

Environmental and real-life conditions

Ambient conditions

Optimum ambient temperature (storage/transport)	23 °C 50 % Polyamide 6.6 has pronounced hygroscopic properties. It absorbs or releases water in accordance with the level of humidity within its environment. Its properties are ideal when the percentage of water is 2 - 3%. The packaging, which is tailored specifically to the product concerned, contains the optimum level of moisture. To ensure that the ideal properties are maintained, the following points should be observed during storage: Keep product stored inside sealed original packaging, carry out any product processing soon after breaking open the packaging, avoid direct sunlight, avoid direct heat.
Ambient temperature (operation)	-40 °C ... 85 °C
Ambient temperature (assembly)	-10 °C ... 60 °C
Resistance to UV radiation	no
Short-term temperature	110 °C

Standards and regulations

Cable tie - WT-HF 2,5X98

3240732

<https://www.phoenixcontact.com/pc/products/3240732>



Resistance to UV radiation	no
----------------------------	----

Mounting

Mounting type	Cannot be removed
---------------	-------------------


Cable tie - WT-HF 2,5X98





3240732


<https://www.phoenixcontact.com/pc/products/3240732>


Approvals


 UL Recognized	Nominal Voltage U_N	Nominal Current I_N	Cross Section AWG	Cross Section mm^2
External reference			-	-

 LR	Nominal Voltage U_N	Nominal Current I_N	Cross Section AWG	Cross Section mm^2
External reference			-	-

 BV	Nominal Voltage U_N	Nominal Current I_N	Cross Section AWG	Cross Section mm^2
External reference			-	-

 RINA	Nominal Voltage U_N	Nominal Current I_N	Cross Section AWG	Cross Section mm^2
External reference			-	-

 GL	Nominal Voltage U_N	Nominal Current I_N	Cross Section AWG	Cross Section mm^2
External reference			-	-

 DNV	Nominal Voltage U_N	Nominal Current I_N	Cross Section AWG	Cross Section mm^2
External reference			-	-

Cable tie - WT-HF 2,5X98

3240732

<https://www.phoenixcontact.com/pc/products/3240732>



Classifications

ECLASS

ECLASS-9.0	27140702
ECLASS-10.0.1	27140702
ECLASS-11.0	27140702

ETIM

ETIM 8.0	EC000046
----------	----------

UNSPSC

UNSPSC 21.0	39121700
-------------	----------

Cable tie - WT-HF 2,5X98

3240732

<https://www.phoenixcontact.com/pc/products/3240732>



Environmental Product Compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

Cable tie - WT-HF 2,5X98

3240732

<https://www.phoenixcontact.com/pc/products/3240732>



Accessories

Cable tie tool

Cable tie tool - UNIFOX-CT 4,8 - 1212475

<https://www.phoenixcontact.com/pc/products/1212475>



Cable binder pliers, for plastic cable binders with a width of 2.2 - 4.8 mm, for a material thickness of up to 1.6 mm

Cable tie tool

Cable tie tool - UNIFOX-CT 4,8P - 1212609

<https://www.phoenixcontact.com/pc/products/1212609>



Cable binder pliers, for plastic cable binders with a width of 2.2 - 4.8 mm, for a material thickness of up to 1.6 mm

Phoenix Contact 2022 © - all rights reserved

<https://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG

Flachsmarktstraße 8

D-32825 Blomberg

+49 (0) 5235-3 00

info@phoenixcontact.com