

Crimping pliers - CRIMPFOX CENTRUS 6S



1213144

<https://www.phoenixcontact.com/de/produkte/1213144>

Please be informed that the data shown in this PDF document is generated from our Online Catalog. Please find the complete data in the user documentation. Our General Terms of Use for Downloads are valid.



Crimping pliers, for uninsulated and insulated ferrules, DIN 46228 Part 1 and 4, from 0.14 mm² ... 6 mm², also for TWIN ferrules up to 2 x 4 mm², automatic cross section adjustment, lateral insertion, equipped with fall protection

Your advantages

- Pressure lock ensures consistently high quality crimping results
- Ergonomic handle design ensures comfortable, fatigue-free handling
- With a particularly small handle width, the tool fits perfectly in your hand
- Up to 30 % lower actuation force, thanks to optimized leverage
- Sturdy plastic guard over the head of the pliers protects the tool against damage caused by dropping

Crimping pliers - CRIMPFOX CENTRUS 6S



1213144

<https://www.phoenixcontact.com/de/produkte/1213144>

Commercial Data

Item number	1213144
Packing unit	1 pc
Minimum order quantity	1 pc
Sales Key	N2 - Druck.Zubh.+HandWKZ
Product Key	BH3131
Catalog Page	Page 420 (C-3-2019)
GTIN	4055626212678
Weight per Piece (including packing)	459,2 g
Weight per Piece (excluding packing)	379,2 g
Customs tariff number	82032000
Country of origin	SE

Crimping pliers - CRIMPFOX CENTRUS 6S



1213144

<https://www.phoenixcontact.com/de/produkte/1213144>

Technical Data

Notes

General	DIN 46228-1, DIN 46228-4
Environmental Product Compliance	
California Proposition 65	Further information on California's prop. 65 is available under "Downloads" in the manufacturer's declaration

Product properties

Product type	Crimping tool
Compression	Square crimp

Crimping position 1

Min. cross section	0.14 mm ²
Max. cross section	6 mm ²
AWG min	26
AWG max	10

Electrical properties

Fuse	DIN 46228-1, DIN 46228-4, UL 486F
------	-----------------------------------

Connection data

Conductor connection

Cross section range, metric	0.14 mm ² ... 6 mm ²
Cross section range AWG	26 ... 10

Dimensions

Width	70 mm
Height	21 mm
Length	180 mm

Material specifications

Color	black/green
-------	-------------

Crimping pliers - CRIMPFOX CENTRUS 6S



1213144

<https://www.phoenixcontact.com/de/produkte/1213144>

Approvals



EAC

Approval ID: RU x-DE.xx08.B.02974

Crimping pliers - CRIMPFOX CENTRUS 6S



1213144

<https://www.phoenixcontact.com/de/produkte/1213144>

Classifications

ECLASS

ECLASS-9.0	21043811
ECLASS-10.0.1	21043811
ECLASS-11.0	21043811

ETIM

ETIM 8.0	EC000168
----------	----------

UNSPSC

UNSPSC 21.0	27111500
-------------	----------

Crimping pliers - CRIMPFOX CENTRUS 6S



1213144

<https://www.phoenixcontact.com/de/produkte/1213144>

Accessories

Replacement spring

Replacement spring - CRIMPFOX/ SPR-4 - 1200288

<https://www.phoenixcontact.com/de/produkte/1200288>

Spare recuperating spring



Replacement handle

Replacement handle - CRIMPFOX CENTRUS NC/U-HANDLE - 1202880

<https://www.phoenixcontact.com/de/produkte/1202880>

Replacement upper handle for CRIMPFOX CENTRUS series



Phoenix Contact 2022 © - all rights reserved

<https://www.phoenixcontact.com>

PHOENIX CONTACT Deutschland GmbH

Flachsmarktstraße 8

D-32825 Blomberg

+49 52 35/3-1 20 00

info@phoenixcontact.de