



1) Sensing surface, 2) Housing, 3) Cover, 4) Potentiometer, 5) LED Power, 6) LED function indicator



### Basic features

<b>Additional features</b>	weld-immune (magnetic field 100kA/m)
<b>Approval/Conformity</b>	CE cULus EAC WEEE
<b>Basic standard</b>	IEC 60947-5-2
<b>Scope of delivery</b>	Nut (2x)
<b>Sensitivity</b>	Switching distance adjustable
<b>Series</b>	M30
<b>Trademark</b>	Global

### Display/Operation

<b>Function indicator</b>	yes
<b>Power indicator</b>	yes

### Electrical connection

<b>Connection</b>	M12x1-Male, 3-pin, A-coded
<b>Polarity reversal protected</b>	yes
<b>Protection against device mix-ups</b>	no
<b>Short-circuit protection</b>	yes

### Electrical data

<b>No-load current <math>I_0</math> max. at <math>U_e</math></b>	18 mA
<b>Operating voltage <math>U_b</math></b>	10...30 VDC
<b>Rated insulation voltage <math>U_i</math></b>	75 V DC
<b>Rated operating current <math>I_e</math></b>	100 mA
<b>Rated operating voltage <math>U_e</math> DC</b>	24 V
<b>Ready delay <math>t_v</math> max.</b>	300 ms
<b>Ripple max. (% of <math>U_e</math>)</b>	10 %
<b>Switching frequency</b>	100 Hz
<b>Utilization category</b>	DC -13
<b>Voltage drop static max.</b>	1.5 V

### Environmental conditions

<b>Ambient temperature</b>	-25...85 °C
<b>Contamination scale</b>	1
<b>IP rating</b>	IP67

### Functional safety

<b>MTTF (40 °C)</b>	343 a
---------------------	-------

### Interface

<b>Switching output</b>	PNP normally open (NO)
-------------------------	------------------------

Capacitive Sensors  
**BCS M30B4I2-PSC15D-S04K**  
Order Code: BCS00MR

**BALLUFF**

**Material**

Cover material	PBT PA
Housing material	1.4305 stainless steel PBT
Material sensing surface	PBT

**Range/Distance**

Hysteresis H max. (% of Sr)	15.0 %
Measuring range	2...15 mm
Rated operating distance S <sub>n</sub>	15 mm
Repeat accuracy max. (% of Sr)	2.0 %
Temperature drift max. (% of Sr)	20 % [-5...55 °C]

**Mechanical data**

Dimension	Ø 30 x 79 mm
Installation	for flush mounting
Size	M30x1.5
Thread (A)	M30x1.5
Tightening torque	90 Nm

**Remarks**

The potentiometer does not have a fixed stop, but can be turned endlessly without destroying anything.  
If no change in the switching signal is detected, the potentiometer should be turned forwards or backwards until a signal change occurs at the output.  
For more information about MTTF and B10d see MTTF / B10d Certificate

Indication of the MTTF- / B10d value does not represent a binding composition and/or life expectancy assurance; these are simply experiential values with no warranty implications. These declared values also do not extend the expiration period for defect claims or affect it in any way.

**Connector Drawings**



**Wiring Diagrams**

