

Shock protection - EMPPR (27X15)



0829535

<https://www.phoenixcontact.com/pc/products/0829535>

Please be informed that the data shown in this PDF document is generated from our Online Catalog. Please find the complete data in the user documentation. Our General Terms of Use for Downloads are valid.

Shock protection, Sheet, transparent, unlabeled, mounting type: snap in, lettering field size: 27 x 15 mm



Your advantages

- High level of mechanical and chemical stability
- Suitable for permanent outdoor use
- Stuck or snapped onto labeled CARRIER ... to protect the labeling
- Extremely thick, yet flexible and transparent shock protection

Shock protection - EMPPR (27X15)



0829535

<https://www.phoenixcontact.com/pc/products/0829535>

Commercial Data

Item number	0829535
Packing unit	50 pc
Minimum order quantity	50 pc
Product Key	BG241B
Catalog Page	Page 349 (C-3-2019)
GTIN	4046356614931
Weight per Piece (including packing)	0.193 g
Weight per Piece (excluding packing)	0.1 g
Customs tariff number	39204910
Country of origin	DE

Shock protection - EMPPR (27X15)



0829535

<https://www.phoenixcontact.com/pc/products/0829535>

Technical Data

Product properties

Product type	Cover
--------------	-------

Dimensions

Width	27 mm
Length	15 mm

Material specifications

Color	transparent
RoHS compliant	Yes
Foil strength	300 µm
Material	PVC
Flammability rating according to UL 94	V0
Components	Silicone-free
Silicone-free	Yes

Environmental and real-life conditions

Test for substances that would hinder coating with paint or varnish

	VW PV 3.10.7:2005-02
Result	Test passed

UV resistance

Specification	Following ISO 4892-2:2013-03
Result	Test passed
Test duration	96 h

Testing in a condensation changing climate in the presence of sulfur dioxide

Specification	following DIN 50018:2013-05
Result	Test passed
Climate level	AHT 1,0 S
Cycles	2

Salt spray test

Specification	DIN EN 60068-2-11:2000-02
Result	Test passed

Ambient conditions

Ambient temperature (operation)	-30 °C ... 70 °C
Recommended storage conditions	10-30 °C / 40-70 % relative humidity. Storage in a cool and dry place is recommended.

Standards and regulations

Wipe resistance	DIN EN 61010-1 (VDE 0411-1)
-----------------	-----------------------------

Shock protection - EMPPR (27X15)

0829535

<https://www.phoenixcontact.com/pc/products/0829535>



Mounting

Mounting type

snap in

Shock protection - EMPPR (27X15)



0829535

<https://www.phoenixcontact.com/pc/products/0829535>

Classifications

ECLASS

ECLASS-9.0	27400629
ECLASS-11.0	24292214
ECLASS-10.0.1	27400629

ETIM

ETIM 8.0	EC002113
----------	----------

UNSPSC

UNSPSC 21.0	39131500
-------------	----------

Phoenix Contact 2022 © - all rights reserved

<https://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG

Flachmarktstraße 8

D-32825 Blomberg

+49 (0) 5235-3 00

info@phoenixcontact.com