

Switching lock - S

0308359

<https://www.phoenixcontact.com/de/produkte/0308359>



Please be informed that the data shown in this PDF document is generated from our Online Catalog. Please find the complete data in the user documentation. Our General Terms of Use for Downloads are valid.

Switching lock, for disconnect slides, length: 12 mm, width: 8.2 mm, color: white



Switching lock - S

0308359

<https://www.phoenixcontact.com/de/produkte/0308359>



Commercial Data

Item number	0308359
Packing unit	100 pc
Minimum order quantity	1 pc
Sales Key	A1 - Reihenklennen
Product Key	BE1ZWX
Catalog Page	Page 519 (C-1-2019)
GTIN	4017918000981
Weight per Piece (including packing)	0,869 g
Weight per Piece (excluding packing)	0,814 g
Customs tariff number	85389099
Country of origin	DE

Switching lock - S



0308359

<https://www.phoenixcontact.com/de/produkte/0308359>

Technical Data

Product properties

Product type	Switching lock
--------------	----------------

Dimensions

Width	8.2 mm
Length	12 mm

Material specifications

Color	white
Material	PA
Flammability rating according to UL 94	V2
Insulating material	PA
Relative insulation material temperature index (Elec., UL 746 B)	125 °C

Environmental and real-life conditions

Ambient conditions

Ambient temperature (operation)	-60 °C ... 105 °C (max. short-term operating temperature RTI Elec.)
Ambient temperature (storage/transport)	-25 °C ... 60 °C (for a short time, not exceeding 24 h, -60 °C to +70 °C)
Ambient temperature (assembly)	-5 °C ... 70 °C
Ambient temperature (actuation)	-5 °C ... 70 °C
Permissible humidity (storage/transport)	30 % ... 70 %

Switching lock - S



0308359

<https://www.phoenixcontact.com/de/produkte/0308359>

Classifications

ECLASS

ECLASS-9.0	27141190
ECLASS-10.0.1	27141190
ECLASS-11.0	27141190

ETIM

ETIM 8.0	EC002848
----------	----------

UNSPSC

UNSPSC 21.0	39121400
-------------	----------

Switching lock - S

0308359

<https://www.phoenixcontact.com/de/produkte/0308359>



Environmental Product Compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

Phoenix Contact 2022 © - all rights reserved
<https://www.phoenixcontact.com>

PHOENIX CONTACT Deutschland GmbH
Flachmarktstraße 8
D-32825 Blomberg
+49 52 35/3-1 20 00
info@phoenixcontact.de