

# Housing - HC-STA-B16-HHWD-1STP29-EL-AL



1412706

<https://www.phoenixcontact.com/pc/products/1412706>

Please be informed that the data shown in this PDF document is generated from our Online Catalog. Please find the complete data in the user documentation. Our General Terms of Use for Downloads are valid.

---



Sleeve housing B16, with double locking latch, material: Die-cast aluminum, salt water resistant, cable outlets: 1, lateral, 1x Pg29, height: 76 mm, cable gland: none, Standard

---

## Your advantages

- good shielding in the event of electromagnetic interference

# Housing - HC-STA-B16-HHWD-1STP29-EL-AL



1412706

<https://www.phoenixcontact.com/pc/products/1412706>

## Commercial Data

Item number	1412706
Packing unit	1 pc
Minimum order quantity	1 pc
Product Key	BF7APB
Catalog Page	Page 628 (C-2-2019)
GTIN	4055626059860
Weight per Piece (including packing)	247.5 g
Weight per Piece (excluding packing)	247.5 g
Customs tariff number	85389099
Country of origin	PL

1412706

<https://www.phoenixcontact.com/pc/products/1412706>

## Technical Data


### Notes

General	For contact inserts HC-B16, BB32, D40, DD72, HS6, HV6, M, K
---------	---

### Product properties

Type	B16
Product type	Housing with locking latch
Application	Standard
No. of cable outlets	1
Type of the screw connection	1x Pg29
Housing type	Sleeve housing
Locking type	with double locking latch
Cable outlet	lateral
Pg screw connection	none

### Dimensions

Dimensional drawing	
Width	44 mm
Height	76 mm
Length	93.5 mm

### Internal dimensions

Length of internal thread	14 mm
---------------------------	-------

### Material specifications

Color	gray aluminum
Flammability rating according to UL 94	V0 (Interlock)
Housing surface material	uncoated
Locking latch material	PA
Impact strength	IK09
Housing material	Die-cast aluminum, salt water resistant

### Ambient conditions

Degree of protection	IP66
	IP67
Degree of protection	4 (UL 50e)
	4X (UL 50e)
	12 (UL 50e)
Impact strength	IK09

# Housing - HC-STA-B16-HHWD-1STP29-EL-AL



1412706

<https://www.phoenixcontact.com/pc/products/1412706>

Ambient temperature (operation)	-40 °C ... 125 °C
---------------------------------	-------------------

## Mechanical properties

### Mechanical data


Type of the screw connection	1x Pg29
Locking type	Latch

1412706

<https://www.phoenixcontact.com/pc/products/1412706>

## Drawings

Dimensional drawing



Dimensional drawing

1412706

<https://www.phoenixcontact.com/pc/products/1412706>

## Approvals

**DNV**

Approval ID: TAE000037S



**cUL Recognized**

Approval ID: E255026



**UL Recognized**

Approval ID: E255026



**EAC**

Approval ID: RU C-DE.AI30.B.01102



**EAC**

Approval ID: RU C-DE.BL08.B.00511

**cULus Recognized**

1412706

<https://www.phoenixcontact.com/pc/products/1412706>

## Classifications

### ECLASS

ECLASS-9.0	27440202
ECLASS-10.0.1	27440202
ECLASS-11.0	27440202

### ETIM

ETIM 8.0	EC000437
----------	----------

### UNSPSC

UNSPSC 21.0	31261500
-------------	----------

# Housing - HC-STA-B16-HHWD-1STP29-EL-AL



1412706

<https://www.phoenixcontact.com/pc/products/1412706>

## Environmental Product Compliance

China RoHS	Environmentally Friendly Use Period = 50 years For information on hazardous substances, refer to the manufacturer's declaration available under "Downloads"
------------	--



1412706

<https://www.phoenixcontact.com/pc/products/1412706>

## Accessories

### Cable gland

Cable gland - G-INS-PG29-M68N-NNES-S - 1411176

<https://www.phoenixcontact.com/pc/products/1411176>



Cable gland, cable gland material: Nickel-plated brass, external cable diameter 18 mm ... 25 mm, shielding: no, connecting thread: Pg29, color: silver, with O-ring

---

### Cable gland

Cable gland - G-INSEC-PG29-M68N-NNES-S - 1411201

<https://www.phoenixcontact.com/pc/products/1411201>



Cable gland, cable gland material: Nickel-plated brass, external cable diameter 18 mm ... 25 mm, shielding: yes, connecting thread: Pg29, color: silver, with O-ring

# Housing - HC-STA-B16-HHWD-1STP29-EL-AL

1412706

<https://www.phoenixcontact.com/pc/products/1412706>

## Screw connection

Screw connection - WP-G HF IP66 PG29 BK - 3240893

<https://www.phoenixcontact.com/pc/products/3240893>



Cable gland, Pg thread, IP66 protection, straight

---

## Screw connection

Screw connection - WP-G HF IP69K PG29 BK - 3240879

<https://www.phoenixcontact.com/pc/products/3240879>



Cable gland, Pg thread, IP68/69k protection, straight

# Housing - HC-STA-B16-HHWD-1STP29-EL-AL

1412706

<https://www.phoenixcontact.com/pc/products/1412706>

## Screw connection

Screw connection - WP-GA HF IP66 PG29 BK - 3240921

<https://www.phoenixcontact.com/pc/products/3240921>

Cable gland, Pg thread, IP66 protection, angled



---

## Screw connection

Screw connection - WP-GA HF IP69K PG29 BK - 3240907

<https://www.phoenixcontact.com/pc/products/3240907>

Cable gland, Pg thread, IP68/69k protection, angled



# Housing - HC-STA-B16-HHWD-1STP29-EL-AL

1412706

<https://www.phoenixcontact.com/pc/products/1412706>

## Screw connection

Screw connection - WP-GR HF IP66 PG29 BK - 3240949

<https://www.phoenixcontact.com/pc/products/3240949>



Cable gland, Pg thread, IP66 protection, with strain relief

---

## Screw connection

Screw connection - WP-GR HF IP69K PG29 BK - 3240935

<https://www.phoenixcontact.com/pc/products/3240935>



Cable gland, Pg thread, IP68/69k protection, with strain relief

# Housing - HC-STA-B16-HHWD-1STP29-EL-AL

1412706

<https://www.phoenixcontact.com/pc/products/1412706>

## Screw connection

Screw connection - WP-G PP HF PG29 - 3240993

<https://www.phoenixcontact.com/pc/products/3240993>



Cable gland made from PP with Pg thread, IP65 protection

---

## Screw connection

Screw connection - WP-GT PP HF PG29 - 3241007

<https://www.phoenixcontact.com/pc/products/3241007>



Cable gland made from PP with Pg thread, rotatable, IP54 protection

1412706

<https://www.phoenixcontact.com/pc/products/1412706>

## Screw connection

Screw connection - WP-G BRASS IP40 PG29 - 3241042

<https://www.phoenixcontact.com/pc/products/3241042>



Cable gland made from brass with Pg thread, IP40 protection

---

## Screw connection

Screw connection - WP-GT BRASS PG29 - 3241028

<https://www.phoenixcontact.com/pc/products/3241028>



Cable gland made from brass with Pg thread, rotatable, IP40 protection

# Housing - HC-STA-B16-HHWD-1STP29-EL-AL

1412706

<https://www.phoenixcontact.com/pc/products/1412706>

## Screw connection

Screw connection - WP-G BRASS IP65 PG29 - 3241056

<https://www.phoenixcontact.com/pc/products/3241056>



Cable gland made from brass with Pg thread, IP65 protection

---

## Protective cover

Protective cover - HC-B16-BCSFD-P-BK - 1414629

<https://www.phoenixcontact.com/pc/products/1414629>



Protective cover B16, for double locking latch, protective cover material: PA, height: 18.5 mm, seal: no, diameter of retaining cord eyelet: 40 mm

# Housing - HC-STA-B16-HHWD-1STP29-EL-AL



1412706

<https://www.phoenixcontact.com/pc/products/1412706>

## Housing brackets

Housing brackets - HC-STA-B10-24-DL-PLBK - 1412886

<https://www.phoenixcontact.com/pc/products/1412886>



Double locking latch for B10 / B16 / B24 housing, HC-EVO...AL and HC-STA...AL

---

## Plastic label

Plastic label - US-EMLP (20X9) CUS - 0830085

<https://www.phoenixcontact.com/pc/products/0830085>



Plastic label, can be ordered: by card, white, labeled according to customer specifications, mounting type: adhesive, lettering field size: 20 x 9 mm, Number of individual labels: 75

---

Phoenix Contact 2022 © - all rights reserved

<https://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG

Flachsmarktstraße 8

D-32825 Blomberg

+49 (0) 5235-3 00

[info@phoenixcontact.com](mailto:info@phoenixcontact.com)