

Cable reel - SAC-3P-100,0-PVC/0,25



1501854

<https://www.phoenixcontact.com/pc/products/1501854>

Please be informed that the data shown in this PDF document is generated from our Online Catalog. Please find the complete data in the user documentation. Our General Terms of Use for Downloads are valid.



By the meter, Cable reel, PVC, black RAL 9005, 3-wire, color single wire: brown, blue, black, cable length: 100 m

Cable reel - SAC-3P-100,0-PVC/0,25



1501854

<https://www.phoenixcontact.com/pc/products/1501854>

Commercial Data

Item number	1501854
Packing unit	1 pc
Minimum order quantity	1 pc
Note	Made to Order (non-returnable)
Product Key	BF1LBA
Catalog Page	Page 302 (C-2-2019)
GTIN	4017918813987
Weight per Piece (including packing)	2,440.96 g
Weight per Piece (excluding packing)	2,170.96 g
Customs tariff number	85444995
Country of origin	DE

Cable reel - SAC-3P-100,0-PVC/0,25



1501854

<https://www.phoenixcontact.com/pc/products/1501854>

Technical Data

Product properties

Product type	Cable by the meter
Number of positions	3
Application	Connector
Shielded	no

Cable / line

Cable length	100 m
Cable weight	29 kg/km
Number of positions	3
Shielded	no
Cable type	PVC black [PVC]
Conductor structure signal line	32x 0.10 mm
AWG signal line	24
Conductor cross section	3x 0.25 mm ² (Signal line)
Wire diameter incl. insulation	1.25 mm ±0.02 mm
External cable diameter	4.4 mm ±0.15 mm
Outer sheath, material	PVC
External sheath, color	black RAL 9005
Conductor material	Bare Cu litz wires
Material wire insulation	PVC
Single wire, color	brown, blue, black
Thickness, insulation	≥ 0.23 mm (Core insulation)
Thickness, outer sheath	≥ 0.76 mm
Overall twist	3 wires, twisted
Max. conductor resistance	max. 78 Ω/km (at 20 °C)
Insulation resistance	≥ 100 MΩ*km (at 20 °C)
Nominal voltage, cable	≥ 300 V
Test voltage	≤ 3000 V
Flame resistance	As per UL-Style 2464
Ambient temperature (operation)	-25 °C ... 80 °C (cable, fixed installation) -5 °C ... 80 °C (Cable, flexible installation)

Cable reel - SAC-3P-100,0-PVC/0,25

1501854

<https://www.phoenixcontact.com/pc/products/1501854>



Approvals



EAC

Approval ID: RU D-DE.HB35.B.00371

Cable reel - SAC-3P-100,0-PVC/0,25



1501854

<https://www.phoenixcontact.com/pc/products/1501854>

Classifications

ECLASS

ECLASS-9.0	27062011
ECLASS-10.0.1	27061801
ECLASS-11.0	27061801

ETIM

ETIM 8.0	EC003249
----------	----------

UNSPSC

UNSPSC 21.0	26121600
-------------	----------

Cable reel - SAC-3P-100,0-PVC/0,25



1501854

<https://www.phoenixcontact.com/pc/products/1501854>

Environmental Product Compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

Cable reel - SAC-3P-100,0-PVC/0,25

1501854

<https://www.phoenixcontact.com/pc/products/1501854>



Accessories

Stripping tool

Stripping tool - WIREFOX SAC - 1212623

<https://www.phoenixcontact.com/pc/products/1212623>



Stripping pliers, for halogen-free sensor/actuator cables (SAC cables), with PUR and PVC insulation, from Ø of 4.4 to 7 mm, any stripping length

Phoenix Contact 2022 © - all rights reserved
<https://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG
Flachsmarktstraße 8
D-32825 Blomberg
+49 (0) 5235-3 00
info@phoenixcontact.com