


Cable housing - KGG-MSTB 2,5/ 3

1803947

<https://www.phoenixcontact.com/de/produkte/1803947>

Please be informed that the data shown in this PDF document is generated from our Online Catalog. Please find the complete data in the user documentation. Our General Terms of Use for Downloads are valid.

Cable housing, pitch: 0 mm, number of positions: 3, color: green



Cable housing - KGG-MSTB 2,5/ 3



1803947

<https://www.phoenixcontact.com/de/produkte/1803947>

Commercial Data

Item number	1803947
Packing unit	10 pc
Minimum order quantity	10 pc
Sales Key	E1 - Leiterplattenanschl.
Product Key	AAHZDC
Catalog Page	Page 348 (C-1-2013)
GTIN	4017918046095
Weight per Piece (including packing)	5,74 g
Weight per Piece (excluding packing)	5,5 g
Customs tariff number	85389099
Country of origin	PL

Cable housing - KGG-MSTB 2,5/ 3



1803947

<https://www.phoenixcontact.com/de/produkte/1803947>

Technical Data

Product properties

Product type	Cable housing
Number of positions	3
Pitch	0.00 mm

Material specifications

Color	green
Flammability rating according to UL 94	HB
Insulating material group	I
Insulating material	ABS

Dimensions

Width	19 mm
Height	37 mm
Pitch	0.00 mm

Notes

General	COMBICON connection plugs can be ordered separately.
---------	--

Cable housing - KGG-MSTB 2,5/ 3

1803947

<https://www.phoenixcontact.com/de/produkte/1803947>



Approvals



EAC

Approval ID: B.01687

Cable housing - KGG-MSTB 2,5/ 3



1803947

<https://www.phoenixcontact.com/de/produkte/1803947>

Classifications

ECLASS

ECLASS-9.0	27440392
ECLASS-10.0.1	27440392
ECLASS-11.0	27460402

ETIM

ETIM 8.0	EC002943
----------	----------

UNSPSC

UNSPSC 21.0	39121400
-------------	----------

Cable housing - KGG-MSTB 2,5/ 3



1803947

<https://www.phoenixcontact.com/de/produkte/1803947>

Environmental Product Compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

Cable housing - KGG-MSTB 2,5/ 3

1803947

<https://www.phoenixcontact.com/de/produkte/1803947>

Accessories

Marker for terminal blocks

Marker for terminal blocks - SBS 2,5/7,5 - 1007604

<https://www.phoenixcontact.com/de/produkte/1007604>



Marker for terminal blocks, Card, white, unlabeled, can be labeled with: Marker pen, perforated, mounting type: snap in, snap into flat marker groove, for terminal block width: 7.5 mm, lettering field size: 15 x 7.5 mm, Number of individual labels: 10

PCB connector

PCB connector - MSTB 2,5/ 3-ST - 1754465

<https://www.phoenixcontact.com/de/produkte/1754465>



PCB connector, nominal cross section: 2.5 mm², color: green, nominal current: 12 A, rated voltage (III/2): 320 V, contact surface: Tin, type of contact: Female connector, number of potentials: 3, number of rows: 1, number of positions: 3, number of connections: 3, product range: MSTB 2,5/...-ST, pitch: 5 mm, connection method: Screw connection with tension sleeve, screw head form: L Slotted, conductor/PCB connection direction: 0 °, locking clip: - Locking clip, plug-in system: COMBICON MSTB 2,5, locking: without, mounting: without, type of packaging: packed in cardboard

Cable housing - KGG-MSTB 2,5/ 3

1803947

<https://www.phoenixcontact.com/de/produkte/1803947>

PCB connector

PCB connector - MSTB 2,5/ 3-ST-5,08 - 1757022

<https://www.phoenixcontact.com/de/produkte/1757022>



PCB connector, nominal cross section: 2.5 mm², color: green, nominal current: 12 A, rated voltage (III/2): 320 V, contact surface: Tin, type of contact: Female connector, number of potentials: 3, number of rows: 1, number of positions: 3, number of connections: 3, product range: MSTB 2,5/...-ST, pitch: 5.08 mm, connection method: Screw connection with tension sleeve, screw head form: L Slotted, conductor/PCB connection direction: 0 °, locking clip: - Locking clip, plug-in system: COMBICON MSTB 2,5, locking: without, mounting: without, type of packaging: packed in cardboard

PCB connector

PCB connector - MSTB 2,5/ 3-STF - 1786844

<https://www.phoenixcontact.com/de/produkte/1786844>



PCB connector, nominal cross section: 2.5 mm², color: green, nominal current: 12 A, rated voltage (III/2): 320 V, contact surface: Tin, type of contact: Female connector, number of potentials: 3, number of rows: 1, number of positions: 3, number of connections: 3, product range: MSTB 2,5/...-STF, pitch: 5 mm, connection method: Screw connection with tension sleeve, screw head form: L Slotted, conductor/PCB connection direction: 0 °, locking clip: - without locking clip, plug-in system: COMBICON MSTB 2,5, locking: Screw locking, mounting: Screw flange, type of packaging: packed in cardboard

Cable housing - KGG-MSTB 2,5/ 3

1803947

<https://www.phoenixcontact.com/de/produkte/1803947>

PCB connector

PCB connector - MSTB 2,5/ 3-STF-5,08 - 1777992

<https://www.phoenixcontact.com/de/produkte/1777992>



PCB connector, nominal cross section: 2.5 mm², color: green, nominal current: 12 A, rated voltage (III/2): 320 V, contact surface: Tin, type of contact: Female connector, number of potentials: 3, number of rows: 1, number of positions: 3, number of connections: 3, product range: MSTB 2,5/...-STF, pitch: 5.08 mm, connection method: Screw connection with tension sleeve, screw head form: L Slotted, conductor/PCB connection direction: 0 °, locking clip: - without locking clip, plug-in system: COMBICON MSTB 2,5, locking: Screw locking, mounting: Screw flange, type of packaging: packed in cardboard

PCB connector

PCB connector - IC 2,5/ 3-ST-5,08 - 1786187

<https://www.phoenixcontact.com/de/produkte/1786187>



PCB connector, nominal cross section: 2.5 mm², color: green, nominal current: 12 A, rated voltage (III/2): 320 V, contact surface: Tin, type of contact: Male connector, number of potentials: 3, number of rows: 1, number of positions: 3, number of connections: 3, product range: IC 2,5/...-ST, pitch: 5.08 mm, connection method: Screw connection with tension sleeve, screw head form: L Slotted, conductor/PCB connection direction: 0 °, locking clip: - without locking clip, plug-in system: COMBICON MSTB 2,5, locking: without, mounting: without, type of packaging: packed in cardboard

Cable housing - KGG-MSTB 2,5/ 3


1803947

<https://www.phoenixcontact.com/de/produkte/1803947>

PCB connector

PCB connector - IC 2,5/ 3-STF-5,08 - 1825323

<https://www.phoenixcontact.com/de/produkte/1825323>



PCB connector, nominal cross section: 2.5 mm², color: green, nominal current: 12 A, rated voltage (III/2): 320 V, contact surface: Tin, type of contact: Male connector, number of potentials: 3, number of rows: 1, number of positions: 3, number of connections: 3, product range: IC 2,5/..-STF, pitch: 5.08 mm, connection method: Screw connection with tension sleeve, screw head form: L Slotted, conductor/PCB connection direction: 0 °, locking clip: - without locking clip, plug-in system: COMBICON MSTB 2,5, locking: Screw locking, mounting: Screw flange, type of packaging: packed in cardboard

PCB connector

PCB connector - GMSTB 2,5/ 2-ST - 1766880

<https://www.phoenixcontact.com/de/produkte/1766880>



PCB connector, nominal cross section: 2.5 mm², color: green, nominal current: 12 A, rated voltage (III/2): 630 V, contact surface: Tin, type of contact: Female connector, number of potentials: 2, number of rows: 1, number of positions: 2, number of connections: 2, product range: GMSTB 2,5/..-ST, pitch: 7.5 mm, connection method: Screw connection with tension sleeve, screw head form: L Slotted, conductor/PCB connection direction: 0 °, locking clip: - Locking clip, plug-in system: COMBICON MSTB 2,5, locking: without, mounting: without, type of packaging: packed in cardboard

Cable housing - KGG-MSTB 2,5/ 3

1803947

<https://www.phoenixcontact.com/de/produkte/1803947>

PCB connector

PCB connector - GMSTB 2,5/ 2-ST-7,62 - 1766990

<https://www.phoenixcontact.com/de/produkte/1766990>



PCB connector, nominal cross section: 2.5 mm², color: green, nominal current: 12 A, rated voltage (III/2): 630 V, contact surface: Tin, type of contact: Female connector, number of potentials: 2, number of rows: 1, number of positions: 2, number of connections: 2, product range: GMSTB 2,5/..-ST, pitch: 7.62 mm, connection method: Screw connection with tension sleeve, screw head form: L Slotted, conductor/PCB connection direction: 0 °, locking clip: - Locking clip, plug-in system: COMBICON MSTB 2,5, locking: without, mounting: without, type of packaging: packed in cardboard

Phoenix Contact 2022 © - all rights reserved

<https://www.phoenixcontact.com>

PHOENIX CONTACT Deutschland GmbH

Flachsmarktstraße 8

D-32825 Blomberg

+49 52 35/3-1 20 00

info@phoenixcontact.de