

Spacer plate - DP-PTRV 4

3270163

<https://www.phoenixcontact.com/de/produkte/3270163>



Please be informed that the data shown in this PDF document is generated from our Online Catalog. Please find the complete data in the user documentation. Our General Terms of Use for Downloads are valid.

Spacer plate, length: 63.6 mm, width: 8.3 mm, height: 54 mm, color: gray



Your advantages

- UC-TMF..., UCT-TMF... that you can mark yourself can be used
- Particularly suitable for accommodating marking material
- Same shape as the PTRV... marshalling panel

Spacer plate - DP-PTRV 4

3270163

<https://www.phoenixcontact.com/de/produkte/3270163>



Commercial Data

Item number	3270163
Packing unit	10 pc
Minimum order quantity	10 pc
Sales Key	A1 - Reihenklennen
Product Key	BE6Z1X
Catalog Page	Page 46 (C-1-2019)
GTIN	4046356796262
Weight per Piece (including packing)	7,39 g
Weight per Piece (excluding packing)	7,18 g
Customs tariff number	39269097
Country of origin	PL

Spacer plate - DP-PTRV 4



3270163

<https://www.phoenixcontact.com/de/produkte/3270163>

Technical Data

Product properties

Product type	Partition plate
--------------	-----------------

Ambient conditions

Ambient temperature (operation)	-60 °C ... 105 °C (max. short-term operating temperature RTI Elec.)
Ambient temperature (storage/transport)	-25 °C ... 60 °C (for a short time, not exceeding 24 h, -60 °C to +70 °C)
Ambient temperature (assembly)	-5 °C ... 70 °C
Ambient temperature (actuation)	-5 °C ... 70 °C
Permissible humidity (storage/transport)	30 % ... 70 %

Material specifications

Color	gray
Material	PA
Flammability rating according to UL 94	V0
Static insulating material application in cold	-60 °C
Temperature index of insulation material (DIN EN 60216-1 (VDE 0304-21))	125 °C
Relative insulation material temperature index (Elec., UL 746 B)	130 °C
Fire protection for rail vehicles (DIN EN 45545-2) R22	HL 1 - HL 3
Fire protection for rail vehicles (DIN EN 45545-2) R23	HL 1 - HL 3
Fire protection for rail vehicles (DIN EN 45545-2) R24	HL 1 - HL 3
Fire protection for rail vehicles (DIN EN 45545-2) R26	HL 1 - HL 3
Calorimetric heat release NFPA 130 (ASTM E 1354)	27,5 MJ/kg
Surface flammability NFPA 130 (ASTM E 162)	passed
Specific optical density of smoke NFPA 130 (ASTM E 662)	passed
Smoke gas toxicity NFPA 130 (SMP 800C)	passed

Dimensions

Width	8.3 mm
Height	54 mm
Length	63.6 mm

Spacer plate - DP-PTRV 4

3270163

<https://www.phoenixcontact.com/de/produkte/3270163>



Classifications

ECLASS

ECLASS-9.0	27141133
ECLASS-10.0.1	27141133
ECLASS-11.0	27141133

ETIM

ETIM 8.0	EC000886
----------	----------

UNSPSC

UNSPSC 21.0	39121400
-------------	----------

Spacer plate - DP-PTRV 4

3270163

<https://www.phoenixcontact.com/de/produkte/3270163>



Environmental Product Compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

Spacer plate - DP-PTRV 4

3270163

<https://www.phoenixcontact.com/de/produkte/3270163>



Accessories

Mounting material

Mounting material - PT-IL - 3208090

<https://www.phoenixcontact.com/de/produkte/3208090>

Operating decal for the push-in Technology



Zack marker strip

Zack marker strip - ZBF 6/9,2 S8:UNBEDRUCKT - 0803447

<https://www.phoenixcontact.com/de/produkte/0803447>



Zack marker strip, Strip, white, unlabeled, can be labeled with: CMS-P1-PLOTTER, PLOTMARK, mounting type: snapped, for terminal block width: 6.2 mm, lettering field size: 10.5 x 6 mm

Spacer plate - DP-PTRV 4

3270163

<https://www.phoenixcontact.com/de/produkte/3270163>



Zack marker strip

Zack marker strip - ZBF 6/9,2 S8 CUS - 8191575

<https://www.phoenixcontact.com/de/produkte/8191575>



Zack marker strip, Strip, white, labeled, mounting type: snap into flat marker groove, for terminal block width: 6.2 mm, lettering field size: 6.15 x 10.5 mm

Zack marker strip

Zack marker strip - ZBF 6/9,2 S8,QR:1-8 - 0803448

<https://www.phoenixcontact.com/de/produkte/0803448>



Zack marker strip, Strip, white, labeled, can be labeled with: CMS-P1-PLOTTER, mounting type: snapped, for terminal block width: 6.2 mm, lettering field size: 10.5 x 6 mm

Spacer plate - DP-PTRV 4

3270163


<https://www.phoenixcontact.com/de/produkte/3270163>



Zack marker strip

Zack marker strip - ZBF 6/9,2 S8,QR:A-H - 0803449

<https://www.phoenixcontact.com/de/produkte/0803449>



Zack marker strip, Strip, white, labeled, can be labeled with: CMS-P1-PLOTTER, mounting type: snapped, for terminal block width: 6.2 mm, lettering field size: 10.5 x 6 mm

Zack marker strip

Zack marker strip - ZBF 6/9,2 S8,LGS:1-8 - 0803450

<https://www.phoenixcontact.com/de/produkte/0803450>



Zack marker strip, Strip, white, labeled, can be labeled with: CMS-P1-PLOTTER, mounting type: snapped, for terminal block width: 6.2 mm, lettering field size: 10.5 x 6 mm

Spacer plate - DP-PTRV 4

3270163

<https://www.phoenixcontact.com/de/produkte/3270163>



Zack marker strip

Zack marker strip - ZBF 6/9,2 S8,LGS:A-H - 0803451

<https://www.phoenixcontact.com/de/produkte/0803451>



Zack marker strip, Strip, white, labeled, can be labeled with: CMS-P1-PLOTTER, mounting type: snapped, for terminal block width: 6.2 mm, lettering field size: 10.5 x 6 mm

Phoenix Contact 2022 © - all rights reserved

<https://www.phoenixcontact.com>

PHOENIX CONTACT Deutschland GmbH

Flachsmarktstraße 8

D-32825 Blomberg

+49 52 35/3-1 20 00

info@phoenixcontact.de