


Micro terminal - MT 1,5-QUATTRO

3001679

<https://www.phoenixcontact.com/de/produkte/3001679>



Please be informed that the data shown in this PDF document is generated from our Online Catalog. Please find the complete data in the user documentation. Our General Terms of Use for Downloads are valid.



Micro terminal, nom. voltage: 400 V, nominal current: 16 A, connection method: Screw connection, 1 level, Rated cross section: 1.5 mm², cross section: 0.14 mm² - 1.5 mm², mounting type: NS 15, color: gray

Your advantages

- Nominal cross section of 1.5 mm²
- Design width of just 4.2 mm
- Space saving thanks to compact design and mounting option on a 15 mm DIN rail
- Clear arrangement thanks to marking of all terminal points
- Snap-on foot for NS 15 DIN rails
- Easy potential distribution thanks to standardized screw bridges in the terminal center

Micro terminal - MT 1,5-QUATTRO

3001679

<https://www.phoenixcontact.com/de/produkte/3001679>



Commercial Data

Item number	3001679
Packing unit	50 pc
Minimum order quantity	50 pc
Sales Key	A1 - Reihenklennen
Product Key	BE1261
Catalog Page	Page 554 (C-1-2019)
GTIN	4017918104375
Weight per Piece (including packing)	4,39 g
Weight per Piece (excluding packing)	4,36 g
Customs tariff number	85369010
Country of origin	TR

Micro terminal - MT 1,5-QUATTRO



3001679

<https://www.phoenixcontact.com/de/produkte/3001679>

Technical Data

Product properties

Product type	Micro terminal block
Number of connections	4
Number of rows	2
Potentials	1

Insulation characteristics

Overvoltage category	III
Degree of pollution	3

Electrical properties

Rated surge voltage	4 kV
Maximum power dissipation for nominal condition	0.56 W

Connection data

Number of connections per level	4
Nominal cross section	1.5 mm ²

1 level

Screw thread	M2
Tightening torque	0.22 ... 0.25 Nm
Stripping length	6 mm
Internal cylindrical gage	A1
Conductor cross section solid	0.14 mm ² ... 1.5 mm ²
Cross section AWG	26 ... 16
Conductor cross section flexible	0.14 mm ² ... 1.5 mm ²
Conductor cross section, flexible [AWG]	26 ... 16
Flexible conductor cross section flexible (ferrule, w/o plastic sleeve)	0.25 mm ² ... 0.75 mm ²
Flexible conductor cross section (ferrule with plastic sleeve)	0.25 mm ² ... 0.75 mm ²
2 conductors with same cross section, solid	0.14 mm ² ... 0.5 mm ²
2 conductors with same cross section, flexible	0.14 mm ² ... 0.5 mm ²
2 conductors with same cross section, flexible, with ferrule without plastic sleeve	0.25 mm ² ... 0.34 mm ²
Nominal current	16 A
Maximum load current	16 A (in case of a 1.5 mm ² conductor cross section, the maximum load current must not be exceeded by the total current of all connected conductors.)
Nominal voltage	400 V
Nominal cross section	1.5 mm ²

Dimensions

Width	4.2 mm
End cover width	1 mm

Micro terminal - MT 1,5-QUATTRO



3001679

<https://www.phoenixcontact.com/de/produkte/3001679>

Height NS 15	30 mm
Height	1.181 "
Length	33.5 mm

Material specifications

Color	gray
Flammability rating according to UL 94	V0
Insulating material group	I
Insulating material	PA
Static insulating material application in cold	-60 °C
Temperature index of insulation material (DIN EN 60216-1 (VDE 0304-21))	130 °C
Relative insulation material temperature index (Elec., UL 746 B)	130 °C
Fire protection for rail vehicles (DIN EN 45545-2) R22	HL 1 - HL 3
Fire protection for rail vehicles (DIN EN 45545-2) R23	HL 1 - HL 3
Fire protection for rail vehicles (DIN EN 45545-2) R24	HL 1 - HL 3
Fire protection for rail vehicles (DIN EN 45545-2) R26	HL 1 - HL 3
Calorimetric heat release NFPA 130 (ASTM E 1354)	28 MJ/kg
Surface flammability NFPA 130 (ASTM E 162)	passed
Specific optical density of smoke NFPA 130 (ASTM E 662)	passed
Smoke gas toxicity NFPA 130 (SMP 800C)	passed

Electrical tests

Surge voltage test

Test voltage setpoint	4.8 kV
Result	Test passed

Temperature-rise test

Requirement temperature-rise test	Increase in temperature ≤ 45 K
Result	Test passed
Short-time withstand current 1.5 mm ²	0.18 kA
Result	Test passed

Power-frequency withstand voltage

Test voltage setpoint	1.89 kV
Result	Test passed

Mechanical properties

Mechanical data

Open side panel	Yes
-----------------	-----

Mechanical tests

Mechanical strength

Result	Test passed
--------	-------------

Micro terminal - MT 1,5-QUATTRO



3001679

<https://www.phoenixcontact.com/de/produkte/3001679>

Attachment on the carrier

DIN rail/fixing support	NS 15
Test force setpoint	1 N
Result	Test passed

Test for conductor damage and slackening

Rotation speed	10 rpm
Revolutions	135
Conductor cross section/weight	0.14 mm ² / 0.2 kg 1.5 mm ² / 0.4 kg
Result	Test passed

Environmental and real-life conditions

Needle-flame test

Time of exposure	30 s
Result	Test passed

Ambient conditions

Ambient temperature (operation)	-60 °C ... 105 °C (max. short-term operating temperature RTI Elec.)
Ambient temperature (storage/transport)	-25 °C ... 60 °C (for a short time, not exceeding 24 h, -60 °C to +70 °C)
Ambient temperature (assembly)	-5 °C ... 70 °C
Ambient temperature (actuation)	-5 °C ... 70 °C
Permissible humidity (storage/transport)	30 % ... 70 %

Standards and regulations

Connection in acc. with standard	IEC 60947-7-1
----------------------------------	---------------

Mounting

Mounting type	NS 15
---------------	-------

Micro terminal - MT 1,5-QUATTRO

3001679

<https://www.phoenixcontact.com/de/produkte/3001679>



Drawings

Circuit diagram



Micro terminal - MT 1,5-QUATTRO




3001679


<https://www.phoenixcontact.com/de/produkte/3001679>

Approvals


 DNV Approval ID: TAE00001CT				
	Nominal Voltage U_N	Nominal Current I_N	Cross Section AWG	Cross Section mm^2
			-	-

 CSA Approval ID: 13631				
	Nominal Voltage U_N	Nominal Current I_N	Cross Section AWG	Cross Section mm^2
	300 V	15 A	28 - 14	-

 EAC Approval ID: RU C-DE.BL08.B.00534				
---	--	--	--	--

 cULus Recognized Approval ID: E60425				
	Nominal Voltage U_N	Nominal Current I_N	Cross Section AWG	Cross Section mm^2
Use group B	300 V	15 A	30 - 14	-
Use group F	400 V	15 A	30 - 14	-
Use group D	300 V	10 A	30 - 14	-

CCA Approval ID: NTR-NL 4239				
	Nominal Voltage U_N	Nominal Current I_N	Cross Section AWG	Cross Section mm^2
	400 V		-	- 1.5

 LR Approval ID: LR2041789TA				
---	--	--	--	--

 BV Approval ID: 07774/E0 BV				
	Nominal Voltage U_N	Nominal Current I_N	Cross Section AWG	Cross Section mm^2
			-	-

Micro terminal - MT 1,5-QUATTRO



3001679

<https://www.phoenixcontact.com/de/produkte/3001679>

Classifications

ECLASS

ECLASS-9.0	27141120
ECLASS-10.0.1	27141120
ECLASS-11.0	27141120

ETIM

ETIM 8.0	EC000897
----------	----------

UNSPSC

UNSPSC 21.0	39121400
-------------	----------

Micro terminal - MT 1,5-QUATTRO

3001679

<https://www.phoenixcontact.com/de/produkte/3001679>



Environmental Product Compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

Micro terminal - MT 1,5-QUATTRO

3001679

<https://www.phoenixcontact.com/de/produkte/3001679>

Accessories

 Note: Applying some accessories below might limit this product.


Fixed bridge

Fixed bridge - FBRN 2-4 N - 3001543

<https://www.phoenixcontact.com/de/produkte/3001543>



Fixed bridge, color: silver

 Max. current carrying capacity: 12 A

Fingers are protected from contact


Fixed bridge

Fixed bridge - FBRN 3-4 N - 3001556

<https://www.phoenixcontact.com/de/produkte/3001556>



Fixed bridge, color: silver

 Max. current carrying capacity: 12 A

Fingers are protected from contact

Micro terminal - MT 1,5-QUATTRO

3001679


<https://www.phoenixcontact.com/de/produkte/3001679>



Fixed bridge

Fixed bridge - FBRN 4-4 N - 3001569

<https://www.phoenixcontact.com/de/produkte/3001569>



Fixed bridge, pitch: 4 mm, color: silver


 Max. current carrying capacity: 12 A

Fingers are protected from contact

Fixed bridge

Fixed bridge - FBRN 5-4 N - 3001572

<https://www.phoenixcontact.com/de/produkte/3001572>



Fixed bridge, color: silver

 Max. current carrying capacity: 12 A

Fingers are protected from contact

Micro terminal - MT 1,5-QUATTRO

3001679


<https://www.phoenixcontact.com/de/produkte/3001679>




Fixed bridge

Fixed bridge - FBRN 6-4 N - 3001585

<https://www.phoenixcontact.com/de/produkte/3001585>



Fixed bridge, color: silver

 Max. current carrying capacity: 12 A

Fingers are protected from contact


Fixed bridge

Fixed bridge - FBRN 7-4 N - 3001598

<https://www.phoenixcontact.com/de/produkte/3001598>



Fixed bridge, color: silver

 Max. current carrying capacity: 12 A

Fingers are protected from contact

Micro terminal - MT 1,5-QUATTRO

3001679

<https://www.phoenixcontact.com/de/produkte/3001679>

Fixed bridge

Fixed bridge - FBRN 8-4 N - 3001608

<https://www.phoenixcontact.com/de/produkte/3001608>



Fixed bridge, pitch: 4 mm, color: silver

 Max. current carrying capacity: 12 A

Fingers are protected from contact


Fixed bridge

Fixed bridge - FBRN 10-4 N - 3001624

<https://www.phoenixcontact.com/de/produkte/3001624>



Fixed bridge, pitch: 4.2 mm, color: silver

 Max. current carrying capacity: 12 A

Fingers are protected from contact

Micro terminal - MT 1,5-QUATTRO

3001679


<https://www.phoenixcontact.com/de/produkte/3001679>



Fixed bridge

Fixed bridge - FBRN 20-4 N - 3001637

<https://www.phoenixcontact.com/de/produkte/3001637>



Fixed bridge, color: silver

 Max. current carrying capacity: 12 A

Fingers are protected from contact

End cover

End cover - D-MT 1,5-QUATTRO - 3002982

<https://www.phoenixcontact.com/de/produkte/3002982>



End cover, length: 33.6 mm, width: 1 mm, height: 24.3 mm, color: gray

Micro terminal - MT 1,5-QUATTRO

3001679

<https://www.phoenixcontact.com/de/produkte/3001679>



DIN rail, unperforated

DIN rail, unperforated - NS 15 UNPERF 2000MM VPE 10 - 1401695

<https://www.phoenixcontact.com/de/produkte/1401695>



DIN rail, unperforated, acc. to EN 60715, material: Steel, galvanized, passivated with a thick layer, Standard profile, color: silver, Pack of 10 (20 m)

Screwdriver

Screwdriver - SZS 0,4X2,5 VDE - 1205037

<https://www.phoenixcontact.com/de/produkte/1205037>



Screwdriver, slot-headed, VDE insulated, size: 0.4 x 2.5 x 80 mm, 2-component grip, with non-slip grip

Micro terminal - MT 1,5-QUATTRO

3001679

<https://www.phoenixcontact.com/de/produkte/3001679>



DIN rail perforated

DIN rail perforated - NS 15 PERF 2000MM VPE 10 - 1401682

<https://www.phoenixcontact.com/de/produkte/1401682>



DIN rail perforated, acc. to EN 60715, material: Steel, galvanized, passivated with a thick layer, Standard profile, color: silver, Pack of 10 (20 m)

DIN rail perforated

DIN rail perforated - NS 15 AL PERF 2000MM VPE 10 - 1401763

<https://www.phoenixcontact.com/de/produkte/1401763>



DIN rail perforated, acc. to EN 60715, material: Aluminum, uncoated, Standard profile, color: silver, Pack of 10 (20 m)

Micro terminal - MT 1,5-QUATTRO

3001679

<https://www.phoenixcontact.com/de/produkte/3001679>



DIN rail perforated

DIN rail perforated - NS 15 WH PERF 2000MM-VPE 10 - 1204096

<https://www.phoenixcontact.com/de/produkte/1204096>



DIN rail perforated, acc. to EN 60715, material: Steel, Galvanized, white passivated, Standard profile, color: silver, Pack of 10 (20 m)

Zack Marker strip, flat

Zack Marker strip, flat - ZBF 4:UNBEDRUCKT - 0808587

<https://www.phoenixcontact.com/de/produkte/0808587>



Zack Marker strip, flat, Strip, white, unlabeled, can be labeled with: CMS-P1-PLOTTER, PLOTMARK, mounting type: snapped, for terminal block width: 4 mm, lettering field size: 4.2 x 5.2 mm, Number of individual labels: 10

Micro terminal - MT 1,5-QUATTRO

3001679

<https://www.phoenixcontact.com/de/produkte/3001679>



Zack Marker strip, flat

Zack Marker strip, flat - ZBF 4 CUS - 0825023

<https://www.phoenixcontact.com/de/produkte/0825023>



Zack Marker strip, flat, can be ordered: Strip, white, labeled according to customer specifications, mounting type: snap into flat marker groove, for terminal block width: 4.2 mm, lettering field size: 4.2 x 5.2 mm, Number of individual labels: 10

Zack Marker strip, flat

Zack Marker strip, flat - ZBF 4,LGS:FORTL.ZAHLEN - 0808626

<https://www.phoenixcontact.com/de/produkte/0808626>



Zack Marker strip, flat, Strip, white, labeled, printed horizontally: consecutive numbers 1 ... 10, 11 ... 20, etc. up to 91 ... 100, mounting type: snapped, for terminal block width: 4 mm, lettering field size: 4.2 x 5.2 mm, Number of individual labels: 10

Micro terminal - MT 1,5-QUATTRO

3001679


<https://www.phoenixcontact.com/de/produkte/3001679>



Zack Marker strip, flat

Zack Marker strip, flat - ZBF 4,QR:FORTL.ZAHLEN - 0808820

<https://www.phoenixcontact.com/de/produkte/0808820>



Zack Marker strip, flat, Strip, white, labeled, Printed vertically: consecutive numbers 1 ... 10, 11 ... 20, etc. up to 91 ... 100, mounting type: snapped, for terminal block width: 4 mm, lettering field size: 4.2 x 5.2 mm, Number of individual labels: 10

Zack Marker strip, flat

Zack Marker strip, flat - ZBF 4,LGS:GERADE ZAHLEN - 0810818

<https://www.phoenixcontact.com/de/produkte/0810818>



Zack Marker strip, flat, Strip, white, labeled, printed horizontally: consecutive even numbers 2 ... 20, 22 ... 40, etc. up to 82 ... 100, mounting type: snapped, for terminal block width: 4 mm, lettering field size: 5.15 x 4.15 mm, Number of individual labels: 10

Micro terminal - MT 1,5-QUATTRO

3001679

<https://www.phoenixcontact.com/de/produkte/3001679>



Zack Marker strip, flat

Zack Marker strip, flat - ZBF 4,LGS:UNGERADE ZAHLEN - 0810850

<https://www.phoenixcontact.com/de/produkte/0810850>



Zack Marker strip, flat, Strip, white, labeled, printed horizontally: Odd numbers 1 - 19, 21 - 39, etc. up to 81 - 99, mounting type: snapped, for terminal block width: 4 mm, lettering field size: 5.15 x 4.15 mm, Number of individual labels: 10

Marker for terminal blocks

Marker for terminal blocks - UC-TMF 4 - 0818166

<https://www.phoenixcontact.com/de/produkte/0818166>



Marker for terminal blocks, Sheet, white, unlabeled, can be labeled with: BLUEMARK ID COLOR, BLUEMARK ID, BLUEMARK CLED, PLOTMARK, CMS-P1-PLOTTER, mounting type: snapped, for terminal block width: 4.2 mm, lettering field size: 3.6 x 5.1 mm, Number of individual labels: 120

Micro terminal - MT 1,5-QUATTRO

3001679

<https://www.phoenixcontact.com/de/produkte/3001679>



Marker for terminal blocks

Marker for terminal blocks - UC-TMF 4 CUS - 0824630

<https://www.phoenixcontact.com/de/produkte/0824630>



Marker for terminal blocks, can be ordered: by sheet, white, labeled according to customer specifications, mounting type: snap into flat marker groove, for terminal block width: 4.2 mm, lettering field size: 3.6 x 5.1 mm, Number of individual labels: 120

Marker for terminal blocks

Marker for terminal blocks - UCT-TMF 4 - 0828742

<https://www.phoenixcontact.com/de/produkte/0828742>



Marker for terminal blocks, Sheet, white, unlabeled, can be labeled with: TOPMARK NEO, TOPMARK LASER, BLUEMARK ID COLOR, BLUEMARK ID, BLUEMARK CLED, THERMOMARK PRIME, THERMOMARK CARD 2.0, THERMOMARK CARD, mounting type: snapped, for terminal block width: 4.2 mm, lettering field size: 3.4 x 4.7 mm, Number of individual labels: 90

Micro terminal - MT 1,5-QUATTRO

3001679

<https://www.phoenixcontact.com/de/produkte/3001679>

Marker for terminal blocks

Marker for terminal blocks - UCT-TMF 4 CUS - 0829651

<https://www.phoenixcontact.com/de/produkte/0829651>




Marker for terminal blocks, can be ordered: by sheet, white, labeled according to customer specifications, mounting type: snap into flat marker groove, for terminal block width: 4.2 mm, lettering field size: 3.4 x 4.7 mm, Number of individual labels: 90

End clamp

End clamp - E/MBK - 1401637

<https://www.phoenixcontact.com/de/produkte/1401637>



End clamp, width: 6.2 mm, color: gray

Micro terminal - MT 1,5-QUATTRO

3001679

<https://www.phoenixcontact.com/de/produkte/3001679>



End clamp

End clamp - E/MK - 1421633

<https://www.phoenixcontact.com/de/produkte/1421633>

End clamp, width: 6.2 mm, color: gray




End clamp

End clamp - E/MK 1 - 1421659

<https://www.phoenixcontact.com/de/produkte/1421659>

End clamp width: 6 mm, color: gray



Micro terminal - MT 1,5-QUATTRO

3001679

<https://www.phoenixcontact.com/de/produkte/3001679>



Test adapter

Test adapter - PAI-4 - 3030925

<https://www.phoenixcontact.com/de/produkte/3030925>



Test adapter, Touch proof against unintentional direct contact according to DIN EN 50274 when plugged in, for 4 mm test plug and terminal blocks with 4.2 mm pitch, color: gray

Phoenix Contact 2022 © - all rights reserved

<https://www.phoenixcontact.com>

PHOENIX CONTACT Deutschland GmbH

Flachsmarktstraße 8

D-32825 Blomberg

+49 52 35/3-1 20 00

info@phoenixcontact.de