

# Diode block - EMG 45-DIO 8P-1N5408

2954879

<https://www.phoenixcontact.com/pc/products/2954879>

Please be informed that the data shown in this PDF document is generated from our Online Catalog. Please find the complete data in the user documentation. Our General Terms of Use for Downloads are valid.



Diode module, with eight diodes, common cathode, diode type 1N 5408

## Your advantages

- Spark-suppression diodes for limiting surge voltages of inductive loads
- Electrical decoupling of messages in fault reporting systems

## Commercial Data

Item number	2954879
Packing unit	5 pc
Minimum order quantity	1 pc
Product Key	CK4M11
Catalog Page	Page 266 (C-5-2019)
GTIN	4017918085155
Weight per Piece (including packing)	91.58 g
Weight per Piece (excluding packing)	91.58 g
Customs tariff number	85411000
Country of origin	DE

# Diode block - EMG 45-DIO 8P-1N5408



2954879

<https://www.phoenixcontact.com/pc/products/2954879>

## Technical Data

### Product properties

Product type	Diode module
--------------	--------------

### Insulation characteristics

Pollution degree	2
------------------	---

### Input data

#### Diode

Description of the input	8 diodes, common cathode
Diode type	1 N 5408
Peak reverse voltage per diode	1000 V
Reverse current per diode	10 µA
Conducting state voltage per diode	approx. 0.8 V
Conducting state current per diode	1.5 A (with single load) 0.3 A (with simultaneous loads)

### Connection data

Connection method	Screw connection
Stripping length	8 mm
Screw thread	M3
Conductor cross section solid	0.2 mm <sup>2</sup> ... 4 mm <sup>2</sup>
Conductor cross section flexible	0.2 mm <sup>2</sup> ... 2.5 mm <sup>2</sup>
Conductor cross section AWG	24 ... 12

### Dimensions

Width	45 mm
Height	75 mm
Depth	55 mm

### Environmental and real-life conditions

#### Ambient conditions

Ambient temperature (operation)	-20 °C ... 50 °C
Ambient temperature (storage/transport)	-40 °C ... 70 °C

### Approval data

#### CE

Certificate	CE-compliant
Note	and EN 61326

### Standards and regulations

Standards/regulations	DIN EN 50178
-----------------------	--------------

# Diode block - EMG 45-DIO 8P-1N5408



2954879

<https://www.phoenixcontact.com/pc/products/2954879>

## Mounting

Mounting type	DIN rail mounting
Assembly instructions	in rows with zero spacing
Mounting position	any

# Diode block - EMG 45-DIO 8P-1N5408



2954879

<https://www.phoenixcontact.com/pc/products/2954879>

## Approvals



**EAC**

Approval ID: RU\*DE\*08.B.01841/19

# Diode block - EMG 45-DIO 8P-1N5408



2954879

<https://www.phoenixcontact.com/pc/products/2954879>

## Classifications

### ECLASS

ECLASS-9.0	27371010
ECLASS-10.0.1	27371010
ECLASS-11.0	27371010

### ETIM

ETIM 8.0	EC000683
----------	----------

### UNSPSC

UNSPSC 21.0	32151500
-------------	----------

# Diode block - EMG 45-DIO 8P-1N5408



2954879

<https://www.phoenixcontact.com/pc/products/2954879>

## Environmental Product Compliance

REACH SVHC	Lead 7439-92-1
China RoHS	Environmentally Friendly Use Period = 50 years
	For information on hazardous substances, refer to the manufacturer's declaration available under "Downloads"

# Diode block - EMG 45-DIO 8P-1N5408



2954879

<https://www.phoenixcontact.com/pc/products/2954879>

## Accessories

### Marking material

Marking material - EMG-GKS 12 - 2947035

<https://www.phoenixcontact.com/pc/products/2947035>



Device marking label, width: 12 mm, area: 12 x 8 mm, e.g. for EML(10x7) R adhesive marking material

---

Phoenix Contact 2022 © - all rights reserved  
<https://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG  
Flachsmarktstraße 8  
D-32825 Blomberg  
+49 (0) 5235-3 00  
[info@phoenixcontact.com](mailto:info@phoenixcontact.com)