


Plug-in bridge - FBS 50-5 BU

3032114

<https://www.phoenixcontact.com/de/produkte/3032114>



Please be informed that the data shown in this PDF document is generated from our Online Catalog. Please find the complete data in the user documentation. Our General Terms of Use for Downloads are valid.



Plug-in bridge, Version with single- or double-sided cutting edge. Please keep in mind the possible impact on touch protection as well as air clearances and creepage distances., pitch: 5.2 mm, color: blue

Your advantages

- The 2- to 50-pos. jumpers can bridge up to 50 terminal blocks in the two bridge shafts of the CLIPLINE complete system in one step

Plug-in bridge - FBS 50-5 BU



3032114

<https://www.phoenixcontact.com/de/produkte/3032114>

Commercial Data

| | |
|--------------------------------------|---------------------|
| Item number | 3032114 |
| Packing unit | 10 pc |
| Minimum order quantity | 10 pc |
| Sales Key | A1 - Reihenklennen |
| Product Key | BE2Z2X |
| Catalog Page | Page 403 (C-1-2019) |
| GTIN | 4017918942045 |
| Weight per Piece (including packing) | 43,925 g |
| Weight per Piece (excluding packing) | 43,66 g |
| Customs tariff number | 85366990 |
| Country of origin | DE |

Technical Data

Notes

| | |
|---------------------|--|
| Note on application | Version with single- or double-sided cutting edge. Please keep in mind the possible impact on touch protection as well as air clearances and creepage distances. |
|---------------------|--|

Product properties

| | |
|---------------------|--------|
| Product type | Jumper |
| Number of positions | 50 |
| Pitch | 5.2 mm |

Electrical properties

| | |
|----------------------|---|
| Maximum load current | 24 A (The current values for the jumpers can deviate when used in different modular terminal blocks. The precise values can be found in the accessories data for the respective modular terminal blocks.) |
|----------------------|---|

Connection data

| | |
|----------------------|---|
| Maximum load current | 24 A (The current values for the jumpers can deviate when used in different modular terminal blocks. The precise values can be found in the accessories data for the respective modular terminal blocks.) |
|----------------------|---|

Dimensions

| | |
|-------|--------|
| Pitch | 5.2 mm |
|-------|--------|

Material specifications

| | |
|--|--------|
| Color | blue |
| Material | Copper |
| Flammability rating according to UL 94 | V0 |
| Insulating material | PA |

Environmental and real-life conditions

Ambient conditions

| | |
|--|---|
| Ambient temperature (operation) | -60 °C ... 105 °C |
| Ambient temperature (storage/transport) | -25 °C ... 60 °C (for a short time, not exceeding 24 h, -60 °C to +70 °C) |
| Ambient temperature (assembly) | -5 °C ... 70 °C |
| Ambient temperature (actuation) | -5 °C ... 70 °C |
| Permissible humidity (storage/transport) | 30 % ... 70 % |

Mounting

| | |
|---------------|------------------|
| Mounting type | Plug-in mounting |
|---------------|------------------|

Plug-in bridge - FBS 50-5 BU



3032114

<https://www.phoenixcontact.com/de/produkte/3032114>

Classifications

ECLASS

| | |
|---------------|----------|
| ECLASS-9.0 | 27141140 |
| ECLASS-10.0.1 | 27141140 |
| ECLASS-11.0 | 27141140 |

ETIM

| | |
|----------|----------|
| ETIM 8.0 | EC000489 |
|----------|----------|

UNSPSC

| | |
|-------------|----------|
| UNSPSC 21.0 | 39121400 |
|-------------|----------|

Plug-in bridge - FBS 50-5 BU

3032114

<https://www.phoenixcontact.com/de/produkte/3032114>



Environmental Product Compliance

| | |
|------------|---|
| China RoHS | Environmentally friendly use period: unlimited = EFUP-e |
| | No hazardous substances above threshold values |

Plug-in bridge - FBS 50-5 BU

3032114

<https://www.phoenixcontact.com/de/produkte/3032114>



Accessories

Front cutter

Front cutter - CUTFOX-FBS - 1212124

<https://www.phoenixcontact.com/de/produkte/1212124>



Cutting tool, for separating individual jumper bars from FBS ... plug-in bridges and EB ... insertion bridges

Protective cap

Protective cap - FBSC - 3012325

<https://www.phoenixcontact.com/de/produkte/3012325>



Covering hood, provides reliable shock protection when using cut-to-length FBS ...-5 and FBS ...-6 bridges, color: red

Phoenix Contact 2022 © - all rights reserved

<https://www.phoenixcontact.com>

PHOENIX CONTACT Deutschland GmbH

Flachsmarktstraße 8

D-32825 Blomberg

+49 52 35/3-1 20 00

info@phoenixcontact.de