

Cable tie - WT-STEEL S 7,9X360

3240815

<https://www.phoenixcontact.com/pc/products/3240815>



Please be informed that the data shown in this PDF document is generated from our Online Catalog. Please find the complete data in the user documentation. Our General Terms of Use for Downloads are valid.



Cable binders, made from rust-free stainless steel (AISI 304), suitable for harsh ambient conditions, with ball lock, for quick and secure bundling and fastening

Cable tie - WT-STEEL S 7,9X360

3240815

<https://www.phoenixcontact.com/pc/products/3240815>



Commercial Data

Item number	3240815
Packing unit	100 pc
Minimum order quantity	100 pc
Product Key	BE7132
Catalog Page	Page 620 (C-3-2019)
GTIN	4046356705639
Weight per Piece (including packing)	7.6 g
Weight per Piece (excluding packing)	7.2 g
Customs tariff number	73269098
Country of origin	GB

Cable tie - WT-STEEL S 7,9X360



3240815

<https://www.phoenixcontact.com/pc/products/3240815>

Technical Data

Product properties

Product type	Cable tie
Type	Steel strip
Tensile strength GRP	1335 N

Dimensions

Width	7.9 mm
Length	360 mm
Max. material thickness	0.25 mm

Material specifications

Color	silver
RoHS compliant	Yes
Material	Stainless steel 1.4301/AISI 304
Components	free from silicone and halogen

Connector

Material	Stainless steel 1.4301/AISI 304
Material	Stainless steel 1.4301/AISI 304

Cable / line

Cable structure

External cable diameter	≤ 102 mm
-------------------------	----------

Mechanical properties

Tensile strength	1335 N
------------------	--------

Environmental and real-life conditions

Ambient conditions

Ambient temperature (operation)	-80 °C ... 538 °C
Ambient temperature (assembly)	-80 °C ... 538 °C
Resistance to UV radiation	yes

Standards and regulations

Resistance to UV radiation	yes
----------------------------	-----

Mounting

Mounting type	Cannot be removed
---------------	-------------------


Cable tie - WT-STEEL S 7,9X360



3240815

<https://www.phoenixcontact.com/pc/products/3240815>

Approvals

 LR	Nominal Voltage U_N	Nominal Current I_N	Cross Section AWG	Cross Section mm^2
External reference			-	-

Cable tie - WT-STEEL S 7,9X360



3240815

<https://www.phoenixcontact.com/pc/products/3240815>

Classifications

ECLASS

ECLASS-9.0	27140702
ECLASS-10.0.1	27140702
ECLASS-11.0	27140702

ETIM

ETIM 8.0	EC000046
----------	----------

UNSPSC

UNSPSC 21.0	39121700
-------------	----------

Cable tie - WT-STEEL S 7,9X360



3240815

<https://www.phoenixcontact.com/pc/products/3240815>

Environmental Product Compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

Cable tie - WT-STEEL S 7,9X360

3240815

<https://www.phoenixcontact.com/pc/products/3240815>



Accessories

Cable tie tool

Cable tie tool - UNIFOX-CT M 7,9 - 1212610

<https://www.phoenixcontact.com/pc/products/1212610>



Cable binder pliers, for steel cable binders with a width of up to 7.9 mm, for a material thickness of up to 0.3 mm

Phoenix Contact 2022 © - all rights reserved
<https://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG
Flachsmarktstraße 8
D-32825 Blomberg
+49 (0) 5235-3 00
info@phoenixcontact.com