

Measuring instrument - EEM-DM357-70



1219095

<https://www.phoenixcontact.com/pc/products/1219095>

Please be informed that the data shown in this PDF document is generated from our Online Catalog. Please find the complete data in the user documentation. Our General Terms of Use for Downloads are valid.

Three-phase energy meter for active power measurement with direct measurement in networks of up to 500 V / 63 A, with S0 output, with digital input, operating temperature up to +70°C and RS-485 interface, certified in accordance with the MID directive



Measuring instrument - EEM-DM357-70



1219095

<https://www.phoenixcontact.com/pc/products/1219095>

Commercial Data

Item number	1219095
Packing unit	1 pc
Minimum order quantity	1 pc
Product Key	CK4C11
GTIN	4063151303501
Weight per Piece (including packing)	494.466 g
Weight per Piece (excluding packing)	494.466 g
Customs tariff number	90283019
Country of origin	IT

Technical Data

Product properties

Product type	Energy meter
--------------	--------------

Insulation characteristics

Protection class	II (EN 50470-1)
Pollution degree	2

Electrical properties

Electric strength	6 kV
	4 kV (EN 50470-3, 7.2)

Supply

Supply voltage range	Supply from the measuring circuit
----------------------	-----------------------------------

Input data

Measurement

Input voltage range	3x 184 V ... 288 V (320 V ... 500 V)
Input current range	0.02 A ... 63 A
Power consumption	3.5 VA (1 W)
Frequency range	45 Hz ... 65 Hz
Start current I_{st}	0.02 A
Minimal current I_{min}	0.25 A
Maximum current I_{max}	63 A
Transient current I_{tr}	0.5 A
Nominal current I_{ref}	5 A
Current transformer load	1.5 mΩ
Energy (EN 50470-3)	Class B
Real energy (IEC 62053-21)	Class 1
Reactive power (IEC 62053-23)	Class 2

Digital

Description of the input	Active opto-isolated
Input voltage range	80 V AC/DC ... 276 V AC/DC

Output data

S0 output

Output description	Passive opto-isolated
Maximum switching voltage	27 V DC
Max. switching current	27 mA
Pulse time	50 ms ±2 ms
Pause time	30 ms ±2 ms
Pulse LED	1000 imp/kWh

Measuring instrument - EEM-DM357-70



1219095

<https://www.phoenixcontact.com/pc/products/1219095>

Meter constant	100 imp/kWh, kVAh, kvarh
----------------	--------------------------

Connection data

Measurement connection

Connection method	Screw connection
Conductor cross section solid	1.5 mm ² ... 35 mm ²

Measurement connection

Connection method	Screw connection
Conductor cross section solid	0.14 mm ² ... 2.5 mm ²

Interfaces

Communication

Communication protocol	Modbus
Communication standard	RS-485
Transmission speed range	300 bps ... 57600 bps
Parity	odd, even, none

Dimensions

Width	72 mm
Height	91 mm
Depth	70 mm

Environmental and real-life conditions

Ambient conditions

Degree of protection	IP51 (Front) IP20 (Connections)
Ambient temperature (operation)	-25 °C ... 70 °C
Ambient temperature (storage/transport)	-25 °C ... 75 °C
Max. permissible relative humidity (operation)	80 %

Approval data

CE

Certificate	CE-compliant
-------------	--------------

CE

Identification	MID-compliant
----------------	---------------

Standards and regulations

Standards/specifications	EN 50470-1 EN 50470-3
--------------------------	--------------------------

Measuring instrument - EEM-DM357-70



1219095

<https://www.phoenixcontact.com/pc/products/1219095>

Approvals

MID

Approval ID: No. 390/MID

Measuring instrument - EEM-DM357-70



1219095

<https://www.phoenixcontact.com/pc/products/1219095>

Classifications

ECLASS

ECLASS-9.0	27142330
ECLASS-10.0.1	27142330
ECLASS-11.0	27142330

ETIM

ETIM 8.0	EC002301
----------	----------

UNSPSC

UNSPSC 21.0	41113600
-------------	----------

Phoenix Contact 2022 © - all rights reserved

<https://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG

Flachmarktstraße 8

D-32825 Blomberg

+49 (0) 5235-3 00

info@phoenixcontact.com