

Measuring instrument - EEM-SB371-C



1158947

<https://www.phoenixcontact.com/pc/products/1158947>

Please be informed that the data shown in this PDF document is generated from our Online Catalog. Please find the complete data in the user documentation. Our General Terms of Use for Downloads are valid.



Multi-functional energy measuring device without display, with direct Rogowski connection and integrated Ethernet and cloud interface for measuring electrical parameters in low-voltage installations up to 690 V.

Measuring instrument - EEM-SB371-C



1158947

<https://www.phoenixcontact.com/pc/products/1158947>

Commercial Data

Item number	1158947
Packing unit	1 pc
Minimum order quantity	1 pc
Note	Made to Order (non-returnable)
Product Key	CK4C21
GTIN	4063151166014
Weight per Piece (including packing)	434 g
Weight per Piece (excluding packing)	408 g
Customs tariff number	90303100
Country of origin	DE

Technical Data

Product properties

Product type	Energy meter
--------------	--------------

Insulation characteristics

Overvoltage category	III (300 V)
Pollution degree	2

Electrical properties

Electrical isolation	IEC 61010-1 (Overvoltage category III at 300 V AC Overvoltage category II at 600 V AC)
	IEC 61010-1 (Overvoltage category III at 300 V AC Overvoltage category II at 600 V AC)
	IEC 61010-1 (Measurement category III at 300 V AC Measurement category II at 600 V AC)
Test voltage	4 kV AC (50 Hz, 1 min.)
Maximum power dissipation for nominal condition	10 VA
Mains type	3-phase (3 or 4-conductor), 2-phase (2-conductor), and single-phase (1-conductor)

Supply

Supply voltage range	100 V AC ... 230 V AC ($\pm 20\%$)
	150 V DC ... 250 V DC ($\pm 20\%$)
Power consumption	≤ 4 W
Nominal frequency	50 Hz ... 60 Hz (AC sine)

Input data

Measuring principle	True r.m.s. value measurement
Measured value	AC sine (50/60 Hz)
Acquisition of harmonics	up to 63rd harmonic
Description of the input	Digital input in accordance with IEC/EN 61131-2 (type 3)
Number	1
Voltage input signal	24 V DC
Voltage input signal	0 V DC ... 30 V DC
Current input signal	2 mA ... 15 mA
Protection	250 mA (fast-blow)

Measurement: Voltage

Input name	Voltage measuring input V1, V2, V3
Input voltage range direct	35 V AC ... 690 V AC (Phase/Phase)
	20 V AC ... 400 V AC (Phase/neutral conductor)
Input voltage range via external transformers	60 V AC ... 2000000 V AC (primary)
	60 V AC ... 400 V AC (secondary)
Surge voltage capacity	760 V AC (Phase/Phase)
Precision	0.2 %

Measuring instrument - EEM-SB371-C



1158947

<https://www.phoenixcontact.com/pc/products/1158947>

Power consumption	< 2 VA
-------------------	--------

Measurement: Current

Input name	Current measurement RC1, RC2, RC3
Input current	4000 A
Input measuring range voltage	500 μ V ... 400 mV (1000 A)
Response threshold from measuring range nominal value	5 A
Operate threshold	500 μ V (5 A)
Precision	0.5 %

Measurement: Power

Precision	1 %
Real energy (IEC 62053-21)	Class 1
Reactive power (IEC 62053-23)	Class 2

Output data

Output description	Digital output in accordance with IEC/EN 61131-2 (type 3)
Number	1
Current output signal	\leq 100 mA
Voltage output signal	24 V DC
Protection	250 mA (fast-blow)

Connection data

Current / voltage / supply

Connection method	Screw connection
Stripping length	8 mm
Screw thread	M3
Conductor cross section solid	0.2 mm ² ... 6 mm ²
Conductor cross section flexible	0.2 mm ² ... 4 mm ²
Conductor cross section AWG	24 ... 10
Torque	0.5 Nm ... 0.6 Nm

Current / voltage / supply

Connection method	Screw connection
Stripping length	7 mm
Screw thread	M3
Conductor cross section solid	0.14 mm ² ... 2.5 mm ²
Conductor cross section flexible	0.14 mm ² ... 1.5 mm ²
Conductor cross section AWG	26 ... 14
Torque	0.5 Nm ... 0.6 Nm

Interfaces

Data: Network interface

Communication protocol	Modbus/TCP
	REST

Measuring instrument - EEM-SB371-C



1158947

<https://www.phoenixcontact.com/pc/products/1158947>

Connection method	RJ45
Data: Network interface	
Communication protocol	MQTT
Connection method	RJ45
Number of connections	2

IoT capabilities

Platform: PROFICLOUD

Supports cloud computing	yes
Protocol / IP-Port	HTTPS / 443
	MQTT / 8883
Smart Services	Device Management Service
	Time Series Data Service

Dimensions

Width	90 mm
Height	80 mm
Depth	82 mm

Environmental and real-life conditions

Ambient conditions

Degree of protection	IP20 (Housing)
Ambient temperature (operation)	-10 °C ... 55 °C
Ambient temperature (storage/transport)	-40 °C ... 70 °C
Altitude	≤ 2000 m
Max. permissible relative humidity (operation)	≤ 95 % (non-condensing)

Approval data

CE

Certificate	CE-compliant
-------------	--------------

CE

Certificate	UKCA-compliant
-------------	----------------

CE

Identification	UL/C-UL Listed UL 61010-1
----------------	---------------------------

UL data

Operating mode	Indoor use
----------------	------------

UL data

Operating mode	Indoor use
----------------	------------

Mounting

Measuring instrument - EEM-SB371-C



1158947

<https://www.phoenixcontact.com/pc/products/1158947>

Mounting type	DIN rail mounting
Mounting position	Horizontal DIN rail

Measuring instrument - EEM-SB371-C



1158947

<https://www.phoenixcontact.com/pc/products/1158947>

Approvals



UL Listed

Approval ID: FILE E 357804



cUL Listed

Approval ID: FILE E 357804



cUL Listed

Approval ID: FILE E 357804



UL Listed

Approval ID: FILE E 357804

cULus Listed

Measuring instrument - EEM-SB371-C



1158947

<https://www.phoenixcontact.com/pc/products/1158947>

Classifications

ECLASS

ECLASS-9.0	27142330
ECLASS-10.0.1	27142330
ECLASS-11.0	27142330

ETIM

ETIM 8.0	EC002301
----------	----------

UNSPSC

UNSPSC 21.0	41113600
-------------	----------

Measuring instrument - EEM-SB371-C



1158947

<https://www.phoenixcontact.com/pc/products/1158947>

Environmental Product Compliance

REACH SVHC

Lead 7439-92-1

Measuring instrument - EEM-SB371-C



1158947

<https://www.phoenixcontact.com/pc/products/1158947>

Accessories

Coil

Coil - PACT RCP-D95 - 2904890

<https://www.phoenixcontact.com/pc/products/2904890>

300 mm long Rogowski coil. The measuring coil diameter when installed is 95 mm. The Rogowski coil is used for AC current measurement for busbars and power lines.



Coil

Coil - PACT RCP-D140 - 2904891

<https://www.phoenixcontact.com/pc/products/2904891>

450 mm long Rogowski coil. The measuring coil diameter when installed is 140 mm. The Rogowski coil is used for AC current measurement for busbars and power lines.



Measuring instrument - EEM-SB371-C

1158947

<https://www.phoenixcontact.com/pc/products/1158947>

Coil

Coil - PACT RCP-D190 - 2904892

<https://www.phoenixcontact.com/pc/products/2904892>

600 mm long Rogowski coil. The measuring coil diameter when installed is 190 mm. The Rogowski coil is used for AC current measurement for busbars and power lines.



Coil

Coil - PACT RCP-D95-5M - 2910322

<https://www.phoenixcontact.com/pc/products/2910322>

300 mm long Rogowski coil. The measuring coil diameter when installed is 95 mm. The Rogowski coil is used for AC current measurement for busbars and power lines.



Measuring instrument - EEM-SB371-C

1158947

<https://www.phoenixcontact.com/pc/products/1158947>

Coil

Coil - PACT RCP-D95-10M - 2910323

<https://www.phoenixcontact.com/pc/products/2910323>

300 mm long Rogowski coil. The measuring coil diameter when installed is 95 mm. The Rogowski coil is used for AC current measurement for busbars and power lines.



Coil

Coil - PACT RCP-D190-10M - 2910324

<https://www.phoenixcontact.com/pc/products/2910324>

600 mm long Rogowski coil. The measuring coil diameter when installed is 190 mm. The Rogowski coil is used for AC current measurement for busbars and power lines.



Measuring instrument - EEM-SB371-C

1158947

<https://www.phoenixcontact.com/pc/products/1158947>

Holder

Holder - PACT RCP-CLAMP - 2904895

<https://www.phoenixcontact.com/pc/products/2904895>



The optional holding device ensures the Rogowski coil is securely seated on busbars with a thickness of 10 ... 15 mm. During installation, the coil housing is pushed onto the flange of the holding device and snaps in automatically.

Phoenix Contact 2022 © - all rights reserved

<https://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG

Flachsmarktstraße 8

D-32825 Blomberg

+49 (0) 5235-3 00

info@phoenixcontact.com