

Sensor/actuator cable - SAC-8P- 5,0-PUR/M12FS



1520369

<https://www.phoenixcontact.com/de/produkte/1520369>

Please be informed that the data shown in this PDF document is generated from our Online Catalog. Please find the complete data in the user documentation. Our General Terms of Use for Downloads are valid.



Sensor/actuator cable, 8-position, PUR halogen-free, black-gray RAL 7021, free cable end, on Socket straight M12, coding: A, cable length: 5 m

Your advantages

- Easy and safe: 100% electrically tested plug-in components

Sensor/actuator cable - SAC-8P- 5,0-PUR/M12FS



1520369

<https://www.phoenixcontact.com/de/produkte/1520369>

Commercial Data

| | |
|--------------------------------------|-------------------------|
| Item number | 1520369 |
| Packing unit | 1 pc |
| Minimum order quantity | 1 pc |
| Sales Key | C1 - Sensor-Aktor-Kabel |
| Product Key | BF1CFA |
| Catalog Page | Page 208 (C-2-2019) |
| GTIN | 4017918944537 |
| Weight per Piece (including packing) | 232,7 g |
| Weight per Piece (excluding packing) | 228,7 g |
| Customs tariff number | 85444290 |
| Country of origin | PL |

Technical Data

Product properties

| | |
|----------------------|-----------------------|
| Product type | Sensor/actuator cable |
| Number of positions | 8 |
| Application | Standard |
| No. of cable outlets | 1 |
| Shielded | no |
| Coding | A - standard |

Insulation characteristics

| | |
|----------------------|----|
| Overvoltage category | II |
| Degree of pollution | 3 |

Material specifications

| | |
|--|---|
| Flammability rating according to UL 94 | HB |
| Sealing material | NBR |
| Material of grip body | TPU, hardly inflammable, self-extinguishing |
| Contact material | CuZn |
| Contact surface material | Ni/Au |
| Contact carrier material | TPU GF |
| Cable gland material | Zinc die-cast, nickel-plated |

Electrical properties

| | |
|-----------------------|----------------------------|
| Contact resistance | $\leq 5 \text{ m}\Omega$ |
| Insulation resistance | $\geq 100 \text{ M}\Omega$ |
| Nominal voltage U_N | 30 V AC |
| | 30 V DC |
| Nominal current I_N | 2 A |
| Protective circuit | unwired |

Connection data

Conductor connection

| | |
|-------------------|---------------------|
| Tightening torque | 0.4 NmM12 connector |
|-------------------|---------------------|

Connector

| | |
|-----------------------------|------------|
| Insertion/withdrawal cycles | ≥ 100 |
|-----------------------------|------------|

Header 1

| | |
|-------------|----------------|
| Head design | free cable end |
|-------------|----------------|

Header 2

| | |
|-------------------|----------|
| Head design | Socket |
| Head cable outlet | straight |
| Head thread type | M12 |

Sensor/actuator cable - SAC-8P- 5,0-PUR/M12FS



1520369

<https://www.phoenixcontact.com/de/produkte/1520369>

| | |
|--------|---|
| Coding | A |
|--------|---|

LED signaling

| | |
|------------------------|----|
| Status display | No |
| Status display present | No |

Cable / line

| | |
|---|--|
| Cable length | 5 m |
| Cable weight | 46 kg/km |
| UL AWM Style | 20549 / 10493 (80°C/300 V) |
| Number of positions | 8 |
| Shielded | no |
| Cable type | PUR halogen-free black [PUR] |
| Conductor structure signal line | 32x 0.10 mm |
| AWG signal line | 24 |
| Conductor cross section | 8x 0.25 mm ² |
| Wire diameter incl. insulation | 1.17 mm ±0.02 mm |
| External cable diameter | 5.9 mm ±0.15 mm |
| Outer sheath, material | PUR |
| External sheath, color | black-gray RAL 7021 |
| Conductor material | Bare Cu litz wires |
| Material wire insulation | PP |
| Single wire, color | white, brown, green, yellow, gray, pink, blue, red |
| Thickness, insulation | ≥ 0.21 mm |
| Thickness, outer sheath | approx. 0.8 mm |
| Overall twist | 8 wires around filler to the core |
| Max. conductor resistance | ≤ 78 Ω/km |
| Insulation resistance | ≥ 1 GΩ*km |
| Wave impedance | 100 Ω +15 % (with 1 MHz) |
| Cable capacity | ≤ 70 pF/m |
| Nominal voltage, cable | ≤ 300 V |
| Test voltage | ≥ 3000 V |
| Minimum bending radius, fixed installation | 8 x D |
| Minimum bending radius, flexible installation | 10 x D |
| Max. bending cycles | 4000000 |
| Halogen-free | in accordance with DIN VDE 0472 part 815 |
| Flame resistance | in accordance with DIN UL-Style 20549 |
| Resistance to oil | in accordance with DIN EN 60811-2-1 |
| Other resistance | Highly resistant to acids, alkaline solutions and solvents hydrolysis and microbe resistant partly UV-resistant in accordance with DIN EN ISO 4892-2-A Low adhesion abrasion-resistant |
| | Flexible cable conduit capable |

Sensor/actuator cable - SAC-8P- 5,0-PUR/M12FS



1520369

<https://www.phoenixcontact.com/de/produkte/1520369>

| | |
|---------------------------------|---|
| Special properties | Silicone-free |
| | Free of substances which would hinder coating with paint or varnish |
| | flexible |
| Ambient temperature (operation) | -40 °C ... 80 °C (cable, fixed installation) |
| | -25 °C ... 80 °C (Cable, flexible installation) |
| Cable weight | 46 kg/km |

Cable structure

| | |
|---------------------------------|--|
| Cable abbreviation | Li9Y11Y |
| Cable type | PUR halogen-free black |
| External cable diameter | 5.90 mm |
| Outer sheath, material | PUR |
| External sheath, color | black-gray RAL 7021 |
| Conductor material | Bare Cu litz wires |
| Conductor structure signal line | 32x 0.10 mm |
| AWG signal line | 24 |
| Material, filler | PE |
| Material wire insulation | PP |
| Thickness, insulation | ≥ 0.21 mm (Core insulation) |
| Wire diameter incl. insulation | 1.17 mm ±0.02 mm |
| Single wire, color | white, brown, green, yellow, gray, pink, blue, red |

Electrical properties

| | |
|-----------------------------|-------------|
| Nominal voltage, cable | 300 V |
| Test voltage, cable | 3000 V |
| Conductor resistance | ≤ 78 Ω/km |
| Cable insulation resistance | ≥ 100 GΩ*km |

Ambient conditions

| | |
|---------------------------------|--|
| Ambient temperature (operation) | -5 °C ... 80 °C (Cable, flexible installation) |
| | -40 °C ... 80 °C (cable, fixed installation) |

Ambient conditions


| | |
|---------------------------------|--|
| Degree of protection | IP65 |
| | IP67 |
| | IP68 |
| Ambient temperature (operation) | -25 °C ... 90 °C (Plug / socket) |
| | -40 °C ... 80 °C (cable, fixed installation) |
| | -5 °C ... 80 °C (Cable, flexible installation) |

Standards and regulations

| | |
|--------------------------|-----------------|
| Standards/specifications | IEC 61076-2-101 |
|--------------------------|-----------------|


Drawings

Dimensional drawing



M12 x 1 socket, straight

Schematic diagram



Pin assignment M12 socket, 8-pos., A-coded, view female side


Sensor/actuator cable - SAC-8P- 5,0-PUR/M12FS

1520369

<https://www.phoenixcontact.com/de/produkte/1520369>



Circuit diagram



Contact assignment of the M12 socket

Sensor/actuator cable - SAC-8P- 5,0-PUR/M12FS




1520369

<https://www.phoenixcontact.com/de/produkte/1520369>

Approvals

| | | | | |
|--|-----------------------|-----------------------|-------------------|-----------------------------|
|  UL Listed Approval ID: FILE E 221474 | | | | |
| | Nominal Voltage U_N | Nominal Current I_N | Cross Section AWG | Cross Section mm^2 |
| | 30 V | 2 A | - | - |

| | | | | |
|---|-----------------------|-----------------------|-------------------|-----------------------------|
|  cUL Listed Approval ID: FILE E 221474 | | | | |
| | Nominal Voltage U_N | Nominal Current I_N | Cross Section AWG | Cross Section mm^2 |
| | 30 V | 2 A | - | - |

| | | | | |
|---|--|--|--|--|
|  EAC Approval ID: RU D-DE.HB35.B.00387 | | | | |
|---|--|--|--|--|

| | | | | |
|---------------------|--|--|--|--|
| cULus Listed | | | | |
|---------------------|--|--|--|--|

Sensor/actuator cable - SAC-8P- 5,0-PUR/M12FS



1520369

<https://www.phoenixcontact.com/de/produkte/1520369>

Classifications

ECLASS

| | |
|---------------|----------|
| ECLASS-9.0 | 27060311 |
| ECLASS-10.0.1 | 27060311 |
| ECLASS-11.0 | 27060311 |

ETIM

| | |
|----------|----------|
| ETIM 8.0 | EC001855 |
|----------|----------|

UNSPSC

| | |
|-------------|----------|
| UNSPSC 21.0 | 26121600 |
|-------------|----------|

Sensor/actuator cable - SAC-8P- 5,0-PUR/M12FS



1520369

<https://www.phoenixcontact.com/de/produkte/1520369>

Environmental Product Compliance

| | |
|------------|---|
| REACH SVHC | Lead 7439-92-1 |
| China RoHS | Environmentally friendly use period: unlimited = EFUP-e |
| | No hazardous substances above threshold values |

1520369

<https://www.phoenixcontact.com/de/produkte/1520369>

Accessories

Insert label

Insert label - PABA WH/23 - 1013779

<https://www.phoenixcontact.com/de/produkte/1013779>




Insert label, Strip, white, unlabeled, can be labeled with: CMS-P1-PLOTTER, mounting type: slide-on, cable diameter range: 1.5 ... 35 mm, lettering field size: 23 x 4 mm, Number of individual labels: 20

Insert label

Insert label - PABA YE/23 - 1013782

<https://www.phoenixcontact.com/de/produkte/1013782>



Insert label, Strip, yellow, unlabeled, can be labeled with: CMS-P1-PLOTTER, mounting type: slide-on, cable diameter range: 1.5 ... 35 mm, lettering field size: 23 x 4 mm, Number of individual labels: 20

Sensor/actuator cable - SAC-8P- 5,0-PUR/M12FS

1520369

<https://www.phoenixcontact.com/de/produkte/1520369>

Marker pen

Marker pen - B-STIFT - 1051993

<https://www.phoenixcontact.com/de/produkte/1051993>



Marker pen, for manual labeling of unprinted Zack strips, smear-proof and waterproof, line thickness 0.5 mm

Diagonal cutter

Diagonal cutter - CUTFOX-S VDE - 1212207

<https://www.phoenixcontact.com/de/produkte/1212207>



Diagonal cutter for hard (piano wire) and soft wires, VDE 1000 V AC/1500 V DC tested

Sensor/actuator cable - SAC-8P- 5,0-PUR/M12FS

1520369

<https://www.phoenixcontact.com/de/produkte/1520369>

Stripping tool

Stripping tool - WIREFOX SAC-1 - 1212757

<https://www.phoenixcontact.com/de/produkte/1212757>



Stripping pliers, for halogen-free sensor/actuator cables (SAC cables), with PUR and PVC insulation, from Ø of 3.2 to 4.4 mm, any stripping length

Stripping tool

Stripping tool - WIREFOX SAC - 1212623

<https://www.phoenixcontact.com/de/produkte/1212623>



Stripping pliers, for halogen-free sensor/actuator cables (SAC cables), with PUR and PVC insulation, from Ø of 4.4 to 7 mm, any stripping length

Sensor/actuator cable - SAC-8P- 5,0-PUR/M12FS

1520369

<https://www.phoenixcontact.com/de/produkte/1520369>

Stripping tool

Stripping tool - WIREFOX 10 - 1212150

<https://www.phoenixcontact.com/de/produkte/1212150>



Stripping tool, for cables and conductors from 0.02 - 10 mm², self-adjusting, stripping length of up to 18 mm, cutting capacity of up to 10 mm² stranded/1.5 mm² solid, replaceable stripping blade

Protective hose adapter

Protective hose adapter - WP-CTA POM 13,0 BK - 1422884

<https://www.phoenixcontact.com/de/produkte/1422884>



Protective hose adapter, for corrugated hoses with a nominal size of 13 (10 x 13), corrugated in parallel

1520369

<https://www.phoenixcontact.com/de/produkte/1520369>

Protective hose

Protective hose - WP-PA HF 13,0 BK - 3240681

<https://www.phoenixcontact.com/de/produkte/3240681>



Protective hose, material: PA 6, filament: without, UV-resistant: yes, flexible, degree of protection: IP68, color: black, inflammability class in acc. with UL 94: V0, inner diameter: 10 mm, Total length: 50 m

Protective hose

Protective hose - WP-PA HF-HB 13,0 BK - 3240839

<https://www.phoenixcontact.com/de/produkte/3240839>



Protective hose, material: PA 6, filament: without, UV-resistant: yes, flexible, degree of protection: IP68, color: black, inflammability class in acc. with UL 94: HB, inner diameter: 10 mm, Total length: 50 m

Sensor/actuator cable - SAC-8P- 5,0-PUR/M12FS

1520369

<https://www.phoenixcontact.com/de/produkte/1520369>

Screw plug

Screw plug - PROT-M12 MS-PA-CHAIN - 1430899

<https://www.phoenixcontact.com/de/produkte/1430899>

M12 sealing cap with fixing band, for sensor cables, for free M12 sockets



Locking clip

Locking clip - SAC-M12-EXCLIP-F - 1558991

<https://www.phoenixcontact.com/de/produkte/1558991>

Locking clip for the socket side of sensor/actuator cables with M12 connector and M12 connectors for assembly, for knurl diameter: 15 mm or for Allen key with a wrench size of 14 mm, prevents the disconnection of plug-in connections without tools



Sensor/actuator cable - SAC-8P- 5,0-PUR/M12FS

1520369

<https://www.phoenixcontact.com/de/produkte/1520369>

Torque screwdriver

Torque screwdriver - TSD 04 SAC - 1208429

<https://www.phoenixcontact.com/de/produkte/1208429>



Torque screwdriver, with preset torque of 0.4 Nm and 4 mm hexagonal drive for M12 connectors

Torque screwdriver

Torque screwdriver - TSD-M 1,2NM - 1212224

<https://www.phoenixcontact.com/de/produkte/1212224>



Torque screw driver, accuracy as per EN ISO 6789 standard, adjustable from 0.3 - 1.2 Nm

Sensor/actuator cable - SAC-8P- 5,0-PUR/M12FS



1520369

<https://www.phoenixcontact.com/de/produkte/1520369>

Adapter insert

Adapter insert - TSD-M SAC-BIT ADAPTER - 1212600

<https://www.phoenixcontact.com/de/produkte/1212600>



Adapter bit for TSD-M...torque tools, E6.3-1/4" drive with 4 mm hexagon to accommodate SAC bits

Tool

Tool - SAC BIT M12-D15 - 1208432

<https://www.phoenixcontact.com/de/produkte/1208432>



Nut for assembling sensor/actuator cables with M12 connector and M12 connectors for assembly, with a knurl diameter of 15 mm, for 4 mm hexagonal drive

Phoenix Contact 2022 © - all rights reserved
<https://www.phoenixcontact.com>

PHOENIX CONTACT Deutschland GmbH
Flachsmarktstraße 8
D-32825 Blomberg
+49 52 35/3-1 20 00
info@phoenixcontact.de