


Interface module - FLKM-D25 SUB/S



2281144

<https://www.phoenixcontact.com/pc/products/2281144>

Please be informed that the data shown in this PDF document is generated from our Online Catalog. Please find the complete data in the user documentation. Our General Terms of Use for Downloads are valid.



VARIOFACE module, with screw connection and D-Subminiature pin strip, for mounting on NS 35/7.5 or NS 32, 25-pos.

Commercial Data

Item number	2281144
Packing unit	5 pc
Minimum order quantity	1 pc
Product Key	CK2222
Catalog Page	Page 248 (IF-2007)
GTIN	4017918054595
Weight per Piece (including packing)	151 g
Weight per Piece (excluding packing)	151 g
Customs tariff number	85369010
Country of origin	DE

Interface module - FLKM-D25 SUB/S



2281144

<https://www.phoenixcontact.com/pc/products/2281144>

Technical Data

Product properties

Product type	Interface module
Number of positions	25

Insulation characteristics

Overvoltage category	II
Pollution degree	2
Insulation	Functional insulation

Electrical properties

Nominal voltage U_N	25 V AC
	60 V DC
Max. current carrying capacity per branch	2.5 A
	1.5 A (with even load on all branches)
Rated insulation voltage	125 V
Rated surge voltage	1.2 kV

Connection data

Field level

Connection in acc. with standard	IEC / EN
Connection method	Screw connection
Stripping length	8 mm
Screw thread	M3
Conductor cross section solid	0.2 mm ² ... 4 mm ²
Conductor cross section flexible	0.2 mm ² ... 2.5 mm ²
Conductor cross section AWG	24 ... 12

Controller level

Connection method	D-SUB pin strip
Number of positions	25

LED signaling

Status display present	No
------------------------	----

Dimensions

Width	79 mm
Height	77 mm
Depth	57.5 mm

Material specifications

Housing insulation material	Polyamide 6 green
-----------------------------	-------------------

Interface module - FLKM-D25 SUB/S



2281144

<https://www.phoenixcontact.com/pc/products/2281144>

Environmental and real-life conditions

Ambient conditions

Degree of protection	IP20
Ambient temperature (operation)	-20 °C ... 50 °C
Ambient temperature (storage/transport)	-20 °C ... 70 °C

Approval data

UKCA

Certificate	UKCA-compliant
-------------	----------------

Standards and regulations

Standards/regulations	IEC 60664
	DIN EN 50178

Mounting

Mounting type	DIN rail mounting
Mounting position	any

Interface module - FLKM-D25 SUB/S


2281144

<https://www.phoenixcontact.com/pc/products/2281144>



Drawings

Circuit diagram




Interface module - FLKM-D25 SUB/S




2281144

<https://www.phoenixcontact.com/pc/products/2281144>

Approvals

 cUL Recognized Approval ID: FILE E 118976				
	Nominal Voltage U_N	Nominal Current I_N	Cross Section AWG	Cross Section mm^2
Field wiring	125 V	2.5 A	30 - 12	-

 UL Recognized Approval ID: FILE E 118976				
	Nominal Voltage U_N	Nominal Current I_N	Cross Section AWG	Cross Section mm^2
Field wiring	125 V	2.5 A	30 - 12	-

cULus Recognized

Interface module - FLKM-D25 SUB/S



2281144

<https://www.phoenixcontact.com/pc/products/2281144>

Classifications

ECLASS

ECLASS-9.0	27141152
ECLASS-10.0.1	27141152
ECLASS-11.0	27141152

ETIM

ETIM 8.0	EC002780
----------	----------

UNSPSC

UNSPSC 21.0	39121400
-------------	----------

Interface module - FLKM-D25 SUB/S



2281144

<https://www.phoenixcontact.com/pc/products/2281144>

Environmental Product Compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

Interface module - FLKM-D25 SUB/S

2281144

<https://www.phoenixcontact.com/pc/products/2281144>

Accessories

Cable

Cable - CABLE D-SUB-S/.../.../... - 2302340

<https://www.phoenixcontact.com/pc/products/2302340>



Shielded round cable, assembled with one D-SUB male and one female connector, variable cable length

Cable

Cable - CABLE D-SUB-B-B-S/.../.../... - 2302421

<https://www.phoenixcontact.com/pc/products/2302421>



Shielded round cable, assembled with two D-SUB female connectors, variable cable length

Interface module - FLKM-D25 SUB/S

2281144

<https://www.phoenixcontact.com/pc/products/2281144>

Cable

Cable - CABLE-D25SUB/B/S/ 50/KONFEK/S - 2302120

<https://www.phoenixcontact.com/pc/products/2302120>



Assembled shielded round cable; connection 1: D-SUB socket strip (1x 25-position); connection 2: D-SUB pin strip (1x 25-position); cable length: 0.5 m

Cable

Cable - CABLE-D25SUB/B/S/100/KONFEK/S - 2302133

<https://www.phoenixcontact.com/pc/products/2302133>



Assembled shielded round cable; connection 1: D-SUB socket strip (1x 25-position); connection 2: D-SUB pin strip (1x 25-position); cable length: 1 m

Interface module - FLKM-D25 SUB/S

2281144

<https://www.phoenixcontact.com/pc/products/2281144>

Cable

Cable - CABLE-D25SUB/B/S/150/KONFEK/S - 2302146

<https://www.phoenixcontact.com/pc/products/2302146>



Assembled shielded round cable; connection 1: D-SUB socket strip (1x 25-position); connection 2: D-SUB pin strip (1x 25-position); cable length: 1.5 m

Cable

Cable - CABLE-D25SUB/B/S/200/KONFEK/S - 2302159

<https://www.phoenixcontact.com/pc/products/2302159>



Assembled shielded round cable; connection 1: D-SUB socket strip (1x 25-position); connection 2: D-SUB pin strip (1x 25-position); cable length: 2 m

Interface module - FLKM-D25 SUB/S

2281144

<https://www.phoenixcontact.com/pc/products/2281144>

Cable

Cable - CABLE-D25SUB/B/S/300/KONFEK/S - 2302162

<https://www.phoenixcontact.com/pc/products/2302162>



Assembled shielded round cable; connection 1: D-SUB socket strip (1x 25-position); connection 2: D-SUB pin strip (1x 25-position); cable length: 3 m

Cable

Cable - CABLE-D25SUB/B/S/400/KONFEK/S - 2302175

<https://www.phoenixcontact.com/pc/products/2302175>



Assembled shielded round cable; connection 1: D-SUB socket strip (1x 25-position); connection 2: D-SUB pin strip (1x 25-position); cable length: 4 m

Interface module - FLKM-D25 SUB/S

2281144

<https://www.phoenixcontact.com/pc/products/2281144>

Cable

Cable - CABLE-D25SUB/B/S/600/KONFEK/S - 2302188

<https://www.phoenixcontact.com/pc/products/2302188>



Assembled shielded round cable; connection 1: D-SUB socket strip (1x 25-position); connection 2: D-SUB pin strip (1x 25-position); cable length: 6 m

Cable

Cable - CABLE-D25SUB/B/S/HF/S/ 1,0M - 1066665

<https://www.phoenixcontact.com/pc/products/1066665>



Assembled, shielded, halogen-free round cable; connection 1: D-SUB socket strip (1x 25-position); connection 2: D-SUB pin strip (1x 25-position); cable length: 1 m

Interface module - FLKM-D25 SUB/S

2281144

<https://www.phoenixcontact.com/pc/products/2281144>

Cable

Cable - CABLE-D25SUB/B/S/HF/S/ 2,0M - 1066666

<https://www.phoenixcontact.com/pc/products/1066666>



Assembled, shielded, halogen-free round cable; connection 1: D-SUB socket strip (1x 25-position); connection 2: D-SUB pin strip (1x 25-position); cable length: 2 m

Cable

Cable - CABLE-D25SUB/B/S/HF/S/ 3,0M - 1066667

<https://www.phoenixcontact.com/pc/products/1066667>



Assembled, shielded, halogen-free round cable; connection 1: D-SUB socket strip (1x 25-position); connection 2: D-SUB pin strip (1x 25-position); cable length: 3 m

Interface module - FLKM-D25 SUB/S

2281144

<https://www.phoenixcontact.com/pc/products/2281144>

Cable

Cable - CABLE-D25SUB-B-S-HF-S/... - 1075559

<https://www.phoenixcontact.com/pc/products/1075559>



Assembled, shielded, halogen-free round cable; connection 1: D-SUB socket strip (1x 25-position); connection 2: D-SUB pin strip (1x 25-position); cable length: variable

Cable

Cable - CABLE-D-25SUB/F/OE/0,25/S/0,5M - 2926153

<https://www.phoenixcontact.com/pc/products/2926153>



Assembled shielded round cable; connection 1: Single wires (25-position) (The wires are marked and fitted with ferrules. The braided shield is routed to a separate cable end.); connection 2: D-SUB socket strip (1x 25-position); cable length: 0.5 m

Interface module - FLKM-D25 SUB/S

2281144

<https://www.phoenixcontact.com/pc/products/2281144>

Cable

Cable - CABLE-D-25SUB/F/OE/0,25/S/1,0M - 2926166

<https://www.phoenixcontact.com/pc/products/2926166>



Assembled shielded round cable; connection 1: Single wires (25-position) (The wires are marked and fitted with ferrules. The braided shield is routed to a separate cable end.); connection 2: D-SUB socket strip (1x 25-position); cable length: 1 m

Cable

Cable - CABLE-D-25SUB/F/OE/0,25/S/1,5M - 2926179

<https://www.phoenixcontact.com/pc/products/2926179>



Assembled shielded round cable; connection 1: Single wires (25-position) (The wires are marked and fitted with ferrules. The braided shield is routed to a separate cable end.); connection 2: D-SUB socket strip (1x 25-position); cable length: 1.5 m

Interface module - FLKM-D25 SUB/S

2281144

<https://www.phoenixcontact.com/pc/products/2281144>

Cable

Cable - CABLE-D-25SUB/F/OE/0,25/S/2,0M - 2926182

<https://www.phoenixcontact.com/pc/products/2926182>



Assembled shielded round cable; connection 1: Single wires (25-position) (The wires are marked and fitted with ferrules. The braided shield is routed to a separate cable end.); connection 2: D-SUB socket strip (1x 25-position); cable length: 2 m

Cable

Cable - CABLE-D-25SUB/F/OE/0,25/S/3,0M - 2926195

<https://www.phoenixcontact.com/pc/products/2926195>



Assembled shielded round cable; connection 1: Single wires (25-position) (The wires are marked and fitted with ferrules. The braided shield is routed to a separate cable end.); connection 2: D-SUB socket strip (1x 25-position); cable length: 3 m

Interface module - FLKM-D25 SUB/S

2281144

<https://www.phoenixcontact.com/pc/products/2281144>

Cable

Cable - CABLE-D-25SUB/F/OE/0,25/S/4,0M - 2926205

<https://www.phoenixcontact.com/pc/products/2926205>



Assembled shielded round cable; connection 1: Single wires (25-position) (The wires are marked and fitted with ferrules. The braided shield is routed to a separate cable end.); connection 2: D-SUB socket strip (1x 25-position); cable length: 4 m

Cable

Cable - CABLE-D-25SUB/F/OE/0,25/S/6,0M - 2926218

<https://www.phoenixcontact.com/pc/products/2926218>



Assembled shielded round cable; connection 1: Single wires (25-position) (The wires are marked and fitted with ferrules. The braided shield is routed to a separate cable end.); connection 2: D-SUB socket strip (1x 25-position); cable length: 6 m

Interface module - FLKM-D25 SUB/S

2281144

<https://www.phoenixcontact.com/pc/products/2281144>

Cable

Cable - CABLE-D-25SUB/F/OE/0,25/S/10M - 2906214

<https://www.phoenixcontact.com/pc/products/2906214>



Assembled shielded round cable; connection 1: Single wires (25-position) (The wires are marked and fitted with ferrules. The braided shield is routed to a separate cable end.); connection 2: D-SUB socket strip (1x 25-position); cable length: 10 m

Cable

Cable - CABLE-D-25SUB/F/OE/0,25/S/15M - 2906215

<https://www.phoenixcontact.com/pc/products/2906215>



Assembled shielded round cable; connection 1: Single wires (25-position) (The wires are marked and fitted with ferrules. The braided shield is routed to a separate cable end.); connection 2: D-SUB socket strip (1x 25-position); cable length: 15 m

Interface module - FLKM-D25 SUB/S

2281144

<https://www.phoenixcontact.com/pc/products/2281144>

Cable

Cable - CABLE-D-25SUB/F/OE/0,25/S/20M - 2906216

<https://www.phoenixcontact.com/pc/products/2906216>



Assembled shielded round cable; connection 1: Single wires (25-position) (The wires are marked and fitted with ferrules. The braided shield is routed to a separate cable end.); connection 2: D-SUB socket strip (1x 25-position); cable length: 20 m

Cable

Cable - CABLE-D-25SUB-F-OE-0,25-S/... - 2900906

<https://www.phoenixcontact.com/pc/products/2900906>



Assembled shielded round cable; connection 1: Single wires (25-position) (The wires are marked and fitted with ferrules. The braided shield is routed to a separate cable end.); connection 2: D-SUB socket strip (1x 25-position); cable length: variable

Phoenix Contact 2022 © - all rights reserved
<https://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG
Flachsmarktstraße 8
D-32825 Blomberg
+49 (0) 5235-3 00
info@phoenixcontact.com