PHT22-PL-YE - LED light

1109039

https://www.phoenixcontact.com/nz/products/1109039

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Indicator, 22 mm, round, yellow, LED integrated, AC/DC 24 ... 240 V, PT Push-in connection

Your advantages

- 22 mm indicator light with push-in mounting
- Large voltage range 24 ... 240 V AC/DC
- High visibility thanks to bright, uniform light
- Available in different colors
- Robust, touch-proof design for industrial applications

Commercial data

Item number	1109039
Packing unit	1 pc
Minimum order quantity	1 pc
Sales key	BE6122
Product key	BE6122
GTIN	4063151018979
Weight per piece (including packing)	18.8 g
Weight per piece (excluding packing)	16.5 g
Country of origin	Information on the country of origin is provided with the delivery.

Technical data

Product properties

Product type	LED display
Number of connections	2

Insulation characteristics

Overvoltage category	III
Degree of pollution	3

Electrical properties

Rated surge voltage	4 kV

Connection data

Connection method	Push-in connection
Stripping length	8 mm
Conductor cross-section rigid	0.5 mm² ... 2.5 mm²
Conductor cross-section flexible	0.5 mm² ... 1.5 mm²
Conductor cross-section, flexible [AWG]	20 ... 16 (converted acc. to IEC)
2 conductors with same cross section, rigid	0.5 mm² ... 2.5 mm²
2 conductors with the same cross-section AWG rigid	20 ... 16 (converted acc. to IEC)
2 conductors with same cross section, flexible	0.5 mm² ... 1.5 mm²
2 conductors with the same cross-section AWG flexible	20 ... 16 (converted acc. to IEC)
2 conductors with the same cross section, flexible, with ferrule with plastic sleeve	0.5 mm² ... 1.5 mm²
Maximum load current	25 mA
Rated insulation voltage	300 V

Dimensions

Width	30 mm
Height	30 mm

Installation dimensions

Installation depth	28.2 mm

Material specifications

Color	yellow

Environmental and real-life conditions

Degree of protection (IP code)

Degree of protection	IP66

Ambient conditions

Degree of protection (Connection terminal blocks)	IP20
Ambient temperature (operation)	-25 °C ... 70 °C

Ambient temperature (storage/transport)	-30 °C ... 85 °C
Permissible humidity (operation)	≤ 95 % ((room temperature 25℃) no condensation)

Standards and regulations


Standards/specifications	IEC 60947-5-1
	GB 14048.5
	UL 60947-5-1

Mounting

Mounting type	Panel mount
Tightening torque	1 Nm ... 1.2 Nm

Drawings

Circuit diagram



Approvals

To download certificates, visit the product detail page: https://www.phoenixcontact.com/nz/products/1109039

cULus Listed
Approval ID: E172140

CCC
Approval ID: 2024010305697836

CCC
Approval ID: 2025010305806583

TÜV Rheinland
Approval ID: R CN21G3UE 001

Classifications

ECLASS

ECLASS-13.0	27371302
ECLASS-15.0	27110350

ETIM

ETIM 10.0	EC000041

Environmental product compliance

EU RoHS

Fulfills EU RoHS substance requirements	Yes, No exemptions

China RoHS

Environment friendly use period (EFUP)	EFUP-E
	No hazardous substances above the limits

EU REACH SVHC

REACH candidate substance (CAS No.)	No substance above 0.1 wt%

Phoenix Contact 2026 © - all rights reserved
https://www.phoenixcontact.com

PHOENIX CONTACT Ltd
Unit 15C, 906-930 Great South Road, Penrose
Auckland 1061
0508 474 636
sales@phoenixcontact.co.nz